

FPT INDUSTRIAL S.p.A.

EXECUTIVE ORDER: U-R-015-0603 New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RFPXL03.4BSD	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems						
[1]: Electronic Direct Injection (DDI), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Exhaust Gas Recirculation (EGR)	None					

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kW-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

	Crit	Smoke Opacity					
Applicable Standard	NMHC+NOx	СО	PM	ACL	LUG	PEAK	
	STD	4.7	5.0	0.03	*	*	*
Tier 4 Final 37 ≤kW < 56	FEL	*	*	*	*	*	*
07 =RVV 100	NTE	5.9	6.2	0.04	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 26th day of January 2024.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Robin U. Lang

ATTACHMENT: ENGINE MODELS

Family: RFPXL03.4BSD EO Number: U-R-015-0603 Date Applicable: 01/02/2024

					Peak Power			Peak Torque					
Model	Code	Trim	Config	Displacement	Power	Speed	peed Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	L	kW	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
F5DFL413B*H	F5DFL413B*H		14	3.4	55	1800	68	309	1500	70	1	N/A	
F5HFL463D*G	F5HFL463D*G		14	3.4	55	1800	69	318	1400	78	1	N/A	
F5DFL463C*G	F5DFL463C*G		14	3.4	43	1800	55	244	1500	60	1	N/A	
F5HFL463C*G	F5HFL463C*G		14	3.4	48	2100	55	260	1400	68	1	N/A	
F5HGL463B*G	F5HGL463B*G		14	3.4	55	2100	63	318	1400	78	1	N/A	
F5DGL463A*G	F5DGL463A*G		14	3.4	55	1800	69	320	1300	80	1	N/A	
F5HFL463A*G	F5HFL463A*G		14	3.4	55	2100	63	314	1400	77	1	N/A	
F5HFL463B*G	F5HFL463B*G		14	3.4	43	2100	51	250	1400	64	1	N/A	
F5HGL463A*G	F5HGL463A*G		14	3.4	55	2100	63	314	1400	77	1	N/A	
F5DFL463B*G	F5DFL463B*G		14	3.4	48	1800	59	275	1500	66	1	N/A	
F5DFL463A*G	F5DFL463A*G		14	3.4	55	1800	69	309	1500	76	1	N/A	