

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RDTAL07.7RJD	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kW-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

Applicable Standard		Criteria				Smoke Opacity		
		NMHC	NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 130 ≤ kW ≤ 560	STD	0.19	0.40	3.5	0.02	*	*	*
	FEL	*	*	*	*	*	*	*
	NTE	0.28	0.60	4.4	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: That the manufacturer has elected to combine engines from the 75 ≤ kW ≤ 560 power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the 130 ≤ kW ≤ 560 power category in accordance with Section 1039.230(e) of the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 11th day of January 2024.


 Robin U. Lang, Chief
 Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: RDTAL07.7RJD EO Number: U-R-016-0158 Date Applicable: 1/2/2024

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	kW	rpm	lb/hr	N-m	rpm	lb/hr	-	-	-
OM936	OM936LA.E5-1		I6	7.7	280	1800	128.7	1550	1400	101.3	1	N/A	
OM936	OM936LA.E5-2		I6	7.7	260	1800	117.3	1450	1400	94.7	1	N/A	
OM936	OM936LA.E5-3		I6	7.7	230	1800	102.2	1300	1400	83	1	N/A	
OM936	OM936LA.E5-4		I6	7.7	210	1800	92.4	1200	1400	76.4	1	N/A	
OM936	OM936LA.E5-5		I6	7.7	195	1800	85.2	1100	1400	69.2	1	N/A	
OM936	OM936LA.E5-6		I6	7.7	180	1800	78.1	1000	1400	63.2	1	N/A	
OM934	OM934LA.E5-1		I4	5.1	170	1800	73.1	950	1400	59.9	1	N/A	
OM934	OM934LA.E5-2		I4	5.1	150	1800	63.8	850	1400	52.4	1	N/A	
OM934	OM934LA.E5-3		I4	5.1	129	1800	56.7	750	1400	47	1	N/A	
OM934	OM934LA.E5-4		I4	5.1	115	1800	50.7	675	1400	42.5	1	N/A	