Daimler Truck AG

EXECUTIVE ORDER: U-R-016-0159 New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RDTAL10.6RJD	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kW-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

		Crit	eria	Smoke Opacity				
Applicable Standard	NMHC	NOx	СО	PM	ACL	LUG	PEAK	
	STD	0.19	0.40	3.5	0.02	*	*	*
Tier 4 Final 130 ≤ kW ≤ 560	FEL	*	*	*	*	*	*	*
100 = KVV = 000	NTE	0.28	0.60	4.4	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this _____ day of January 2024.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Robin U. Lang

ATTACHMENT: ENGINE MODELS

Family: RDTAL10.6RJD EO Number: U-R-016-0159 Date Applicable: 1/2/2024

					Peak Power			Peak Torque					
Model	Code	Trim	Config	Displacement	Power	Speed	Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	L	kW	rpm	lb/hr	N-m	rpm	lb/hr	-	-	-
OM470	OM470LA.E5-1		16	10.6	340	1600	146.3	2200	1300	127.5	1	N/A	
OM470	OM470LA.E5-2		16	10.6	320	1600	135.6	2100	1300	119.7	1	N/A	
OM470	OM470LA.E5-3		16	10.6	300	1600	126.3	2000	1300	113.5	1	N/A	
OM470	OM470LA.E5-4		16	10.6	280	1600	116.5	1900	1300	106.5	1	N/A	
OM470	OM470LA.E5-5		16	10.6	260	1600	107.6	1800	1300	100.3	1	N/A	
OM470	OM470LA.E5-6		16	10.6	240	1600	99.2	1700	1300	94.6	1	N/A	