

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RJDXL04.5337	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

Applicable Standard		Criteria				Smoke Opacity		
		NMHC	NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 75 ≤ kW < 130	STD	0.19	0.40	5.0	0.02	*	*	*
	FEL	*	*	*	*	*	*	*
	NTE	0.28	0.60	6.2	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: That the manufacturer has elected to combine engines from the 56 ≤ kW < 130 power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the 75 ≤ kW < 130 power categories in accordance with Section 1039.230(e) of the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 21st day of August 2023.



Robin U. Lang, Chief
Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: RJDXL04.5337 EO Number: U-R-004-0664 Date Applicable: 07/27/2023

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	Liters	kilowatt	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
4045	4045HG551A		I-4	4.5	106	1800	128	562	1800	128	1	N/A	
4045	4045HG551B		I-4	4.5	103	1500	143.7	656	1500	143.7	1	N/A	
4045	4045HG551C		I-4	4.5	86	1800	102.9	456	1800	102.9	1	N/A	
4045	4045HG551D		I-4	4.5	86	1500	118.2	547	1500	143.7	1	N/A	
4045	4045HI551A		I-4	4.5	104	2100	106	575	1550	126	1	N/A	
4045	4045HI551B		I-4	4.5	86	2100	90	554	1550	120	1	N/A	
4045	4045HI551C		I-4	4.5	115	2000	120.3	593	1600	129.9	1	N/A	
4045	4045HI551D		I-4	4.5	107	1900	115.7	577	1600	127	1	N/A	
4045	4045HI551E		I-4	4.5	96	1800	109	554	1600	121	1	N/A	
4045	4045HK551A		I-4	4.5	82	2100	89.4	438	1600	98.7	1	N/A	
4045	4045HK551B		I-4	4.5	86	2100	92.2	461	1600	102.1	1	N/A	
4045	4045HN057A		I-4	4.5	104	2100	106	575	1550	126	1	N/A	
4045	4045HN057B		I-4	4.5	86	2100	90	554	1550	120	1	N/A	
4045	4045HP551A		I-4	4.5	106	1800	128	562	1800	128	1	N/A	
4045	4045HP551B		I-4	4.5	103	1500	143.7	656	1500	143.7	1	N/A	
4045	4045HP551C		I-4	4.5	86	1800	102.9	456	1800	102.9	1	N/A	
4045	4045HP551D		I-4	4.5	86	1500	118.2	547	1500	143.7	1	N/A	
4045	4045HPRNT18A		I-4	4.5	116	2400	111.9	675	1550	148.3	1	N/A	
4045	4045WG501A		I-4	4.5	86	2100	93.9	561	1550	123.9	1	N/A	
4045	4045WG501B		I-4	4.5	66	2100	76.3	421	1550	95.2	1	N/A	
4045	4045WG502		I-4	4.5	85	2000	94.6	495	1600	109.7	1	N/A	
4045	4045WG506		I-4	4.5	110	2000	120.3	586	1600	129.9	1	N/A	