

## **DEERE & COMPANY**

EXECUTIVE ORDER: U-R-004-0666 New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year Engine Family		Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RJDXL09.0313	Diesel	Dedicated	Diesel	Constant Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (\*).

		Crit	eria	Smoke Opacity				
Applicable Standard	Applicable Standard N				PM	ACL	LUG	PEAK
	STD	0.19	0.40	3.5	0.02	*	*	*
Tier 4 Final 130 ≤ kW ≤ 560	FEL	*	*	*	*	*	*	*
100 = KVV = 000	NTE	0.28	0.60	4.4	0.03	*	*	*

**BE IT FURTHER RESOLVED:** Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

**BE IT FURTHER RESOLVED:** For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

**BE IT FURTHER RESOLVED:** The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 2/st day of August 2023.

Robin U. Lang, Chief

**Emissions Certification and Compliance Division** 

Polin U. Lang

## ATTACHMENT: ENGINE MODELS

Family: RJDXL09.0313 EO Number: U-R-004-0666 Date Applicable: 07/28/2023

					Peak Power			Peak Torque					
Model	Code	Trim	Config	Displacement	Power	Speed	Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	Liters	kilowatt	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
6090	6090HFG06A		I-6	9	345	1800	263.2	1830	1800	263.2	1	N/A	
6090	6090HFG06B		I-6	9	300	1500	269.8	1910	1500	269.8	1	N/A	
6090	6090HFG06C		I-6	9	326	1800	247.5	1731	1800	247.5	1	N/A	
6090	6090HFG06D		I-6	9	300	1500	269.5	1910	1500	269.5	1	N/A	
6090	6090HFG06E		I-6	9	273	1800	201.3	1448	1800	201.3	1	N/A	
6090	6090HFG06F		I-6	9	273	1500	243	1737	1500	243	1	N/A	
6090	6090HPRNT7		I-6	9	364	1800	277.6	1934	1800	277.6	1	N/A	