

## **DEERE & COMPANY**

EXECUTIVE ORDER: U-R-004-0667 New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation				
2024	RJDXL09.0333	Diesel	Dedicated	Diesel	Variable and Constant Speed				

Emission Control Systems								
[1,2]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None							

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (\*).

		Crit	eria	Smoke Opacity				
Applicable Standard	NMHC	NOx	СО	PM	ACL	LUG	PEAK	
	STD	0.19	0.40	3.5	0.02	*	*	*
Tier 4 Final 130 ≤ kW ≤ 560	FEL	*	*	*	*	*	*	*
100 = KVV = 000	NTE	0.28	0.60	4.4	0.03	*	*	*

**BE IT FURTHER RESOLVED:** Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

**BE IT FURTHER RESOLVED:** For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

**BE IT FURTHER RESOLVED:** The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this \_\_\_\_\_\_ day of November 2023.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

John U. Lan

## ATTACHMENT: ENGINE MODELS

Family: RJDXL09.0333 EO Number: U-R-004-0667 Date Applicable: 11/06/2023

					Peak Power			Peak Torque					
Model	Code	Trim	Config	Displacement	Power	Speed	Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	Liters	kilowatt	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
6090	6090HDW48		I-6	9	344	2000	222.9	1888	1550	250.8	1	N/A	
6090	6090HFA05		I-6	9	344	2000	222.9	1888	1550	250.8	2	N/A	
6090	6090HFA06		I-6	9	291	1900	194.3	1667	1550	221	2	N/A	
6090	6090HN024		I-6	9	291	1900	194.3	1667	1550	221	2	N/A	
6090	6090HPRNT12		I-6	9	361	2000	233	1982	1550	259	2	N/A	
6090	6090HT027		I-6	9	291	1900	194.3	1667	1550	221	1	N/A	
6090	6090RX501		I-6	9	344	2000	222.9	1888	1550	250.8	2	N/A	
6090	6090RX502		I-6	9	291	1900	194.3	1667	1550	221	2	N/A	
6090	6090RX513		I-6	9	291	1900	194.3	1667	1550	221	2	N/A	
6090	6090WG501		I-6	9	265	1950	172.8	1602	1500	213.7	1	N/A	
6090	6090WG502		I-6	9	315	1800	223.2	1887	1500	254.2	2	N/A	
6090	6090WG504		I-6	9	240	1800	170.5	1400	1400	188.6	1	N/A	