

LIEBHERR MACHINES BULLE SA

EXECUTIVE ORDER: U-R-018-0221 New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation			
2024	RLHAL08.0SWC	Diesel	Dedicated	Diesel	Variable and Constant Speed			

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX), Reductant Quality Sensor (RDQS)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

			Crit	eria	Smoke Opacity			
Applicable Standard	NMHC	NOx	СО	PM	ACL	LUG	PEAK	
	STD	0.19	0.40	3.5	0.02	*	*	*
Tier 4 Final 130 ≤ kW ≤ 560	FEL	*	*	*	*	*	*	*
100 ± KVV ± 000	NTE	0.28	0.60	4.4	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this ____25th___ day of October 2023.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: RLHAL08.0SWC EO Number: U-R-018-0221 Date Applicable: 9/13/2023

					Peak Power		Peak Torque						
Model	Code	Trim	Config	Displacement	Power	Speed	Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	L	hp	rpm	mm3/stroke	lb-ft	rpm	mm3/stroke	-	-	-
D944 A7-05	R04KW7103	N/A	L4	7.964	308	1900	260	1068	1350	297	1	N/A	
D944 A7-05	R04KW7104	N/A	L4	7.964	188	1900	165	730	1350	206	1	N/A	
D944 A7-25	R04KW7101	N/A	L4	7.964	295	1900	249	1055	1350	299	1	N/A	
D944 A7-25	R04KW7102	N/A	L4	7.964	268	1900	229	1055	1350	299	1	N/A	