

## **MOTORENFABRIK HATZ GMBH & CO. KG**

EXECUTIVE ORDER: U-R-034-0349
New Off-Road Compression-Ignition Engines
Page 1 of 1

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RHZXL02.0C51	Diesel	Dedicated	Diesel	Constant Speed Only

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charge Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatthour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (\*).

	Crit	Criteria				Smoke Opacity		
Applicable Standard		NMHC+NOx	СО	PM	ACL	LUG	PEAK	
	STD	4.7	5.0	0.03	*	*	*	
Tier 4 Final 37 ≤ kW < 56	FEL	*	*	*	*	*	*	
07 = KW 4 00	NTE	5.9	6.2	0.04	*	*	*	

**BE IT FURTHER RESOLVED:** Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

**BE IT FURTHER RESOLVED:** That the manufacturer has elected to combine engines from the  $19 \le kW < 56$  power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the 37  $\le kW < 56$  power category in accordance with Section 1039.230(e) of the applicable California test procedures.

**BE IT FURTHER RESOLVED:** For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

**BE IT FURTHER RESOLVED:** The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 20th day of October 2023.

Robin U. Lang. Chief

**Emissions Certification and Compliance Division** 

## ATTACHMENT: ENGINE MODELS

Family: RHZXL02.0C51 EO Number: U-R-034-0349 Date Applicable: 10/11/2023

					Peak Power			Peak Torque					
Model	Code	Trim	Config	Displacement	Power	Speed	Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	L	kW	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
3H50TICD	3H50TICD-cs-15-IFN		13	1.46	25.5	1500	50.5	162.3381	1500	50.5	1	N/A	
3H50TICD	3H50TICD-cs-15-ICFN		13	1.46	22.6	1500	46	143.87612	1500	46	1	N/A	
3H50TICD	3H50TICD-cs-18-IFN		13	1.46	31.3	1800	50.5	166.051717	1800	50.5	1	N/A	
3H50TICD	3H50TICD-cs-18-ICFN		13	1.46	28.5	1800	47	151.19725	1800	47	1	N/A	
4H50TICD	4H50TICD-cs-15-IFN		14	1.95	35	1500	50.5	222.817	1500	50.5	1	N/A	
4H50TICD	4H50TICD-cs-15-ICFN		14	1.95	31	1500	46	197.3522	1500	46	1	N/A	
4H50TICD	4H50TICD-cs-18-IFN		14	1.95	41	1800	49	217.511833	1800	49	1	N/A	
4H50TICD	4H50TICD-cs-18-ICFN		14	1.95	36.4	1800	44	193.108067	1800	44	1	N/A	