State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-23 Relating to Approval of New Motor Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by Sections 39150 and 39151 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Section 39023 of the Health and Safety Code;

IT IS ORDERED AND RESOLVED: That Honda Motor Co., Ltd. exhaust emission control systems for 1973-model year light-duty motor vehicles are approved for the engine families described below:

Engine Family	Engine Size (cubic inches)	Emission Control System	Vehicle Models		
EB '	71.3	Engine Modifications	SB1 2 & 3 Door Sedan		

Section 39152, Part I, Division 26 of the California Health and Safety Code requires that a decal be affixed to the side window which discloses the highest emissions from the certification fleet for that engine family which approval has been granted by the Board.

The following are the recommended values to be listed on the decal:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides			
	Grams per Mile	Grams per Mile	Grams per Mile			
EB	2.1	23	1.7			

These values are in effect until January 30, 1973. After this date, the exhaust emissions for each vehicle determined by factory assembly-line tests in accordance with the "Assembly-Line Test Procedure for 1973 and Subsequent Model Light-Duty Vehicles" must be shown on a decal.

In accordance with Section III E. of the California Exhaust Emission Standards and Test Procedures for 1973 through 1976 Models Gasoline-Powered Light-Duty Motor Vehicles, the manufacturer is required to inform the Air Resources Board of any production changes which will affect emissions.

Supplemental information sheets are attached to this order which include tune-up specifications and emission control system data.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair of the Department of Consumer Affairs will be notified of this approval by copy of this order and attachment.

Executed at Sacramento, California, this and day of Actober, 1972.

JOHN A. MAGA Executive Officer

SUMMEDIATE ALCONOMOS SUME 1973 Indel-Year ATA BIRCOARD

Light Duty Contelles

,								<u> </u>			
	Selection of the select	TCS & CTD TSP	CT0 TSP								
RDER A-23	Evel.	Canister	Canister					 			and the second of the second
EXECUTIVE ORDER A-23	Reheust Nox Reco.					······································					· · · · · · · · · · · · · · · · · · ·
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Erheust Erheust	EΑ	EM				· · · · · · · · · · · · · · · · · · ·	 · <u>·</u>			-
and and the first term of the second	Carburetor Ethe 6 No.	Hitachi OCG 306-45	Hitachi DCG 306-46					 •			
	Type Adv.*	-\^-\ \\ \\	C-V- VR		· · · · · · · · ·			 <u></u>			
でで、 出土の (資配に Winds A) マンコピール	Matributor Ede & No.	Hi tachi 414-66	Hitachi 414-66	<i>:</i>			· :				The second secon
	Trans	M=44	M-2 W/T.C.		•						
HONDA NOTOR CO., LTD.	Carbuxetor No.of Vouturi	1 - 2V	1-2V								
OTON VOXO	Zngtno C, I, D.	71.3	71.3	· .						,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
e estado de la composição de la composiç	j	s81 2 & 3 Door Sedan	581 2 & 3 Door Sedan				,		······		

VR ~ Vacanta recard

a c - c perfora

M = Manual transmission
 T.C.= Torque convertor
 TCS = Transmission controlled spark advance - No vacuum advance in 1st, 2nd & 3rd Gear.

CTO = Ceolant temperature override. No vacuum advance when coolant temperature is above 120°F. Vacuum applied in 4th gear.

TSP = Throttle solenoid positioner

AKK PERKERSE FOARD SERVICE ERACETATION 1973 ERACH-KRAI Right Ducy Vohiolan

EXECUTIVE ORDER A-23	Tungant Specification	Telle CO or AFR	2.0 + 1.0 %	2.0 + 1.0 %				.,	 	<u> </u>	
		Baste Tiring	T. 0. C.	T. D. C.							
		Man of D.		750 + 50 * in 1st Gear							
Carlo Contra de Companyo de Carlo Contra de Carlo Contra de Carlo	Inerta	Halans	1,750	1,750	. ·			 	·		
	Engine	Rently	EB	83							
Publication of State Community of the	- 000001	Jeston.	7-W	M-2 W/T.C.							
HOMBA MOTOR CO., LTD.		Ħ	1-2V	1-2V			•				
HONDA MC	Con Fred Rich	C, I, D,	71.3	71.3			_			·	····
			SB1 2 & 3 Door Sedan	S81 2 & 3 · Door Sedan		and the second s	w 100 mm (

M-4 = Manual Transmission
M-2/T.C. = Torque converter
A = Engine at normal operating temperature with headlights on.

See other aids for additional information.