State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-1 Relating to Approval of New Motor Vehicles

DAIMLER-BENZ, AG.

Pursuant to the authority vested in the Air Resources Board by Section 39150 and 39151 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Section 39023 of the Healty and Safety Code;

IT IS ORDERED AND RESOLVED: That Daimler-Benz, AG. exhaust emission control systems for 1973-model light-duty motor vehicles are approved for the engine families described below:

Engine Family	Engine Size (cubic inches)	Exhaust Emission Control Systems	Vehicle Model	
1	134	Engine Modification & Exhaust Gas Recirculation	MB220	

Section 39152, Part I, Division 26 of the California Health and Safety Code, requires that a decal be affixed to the side window which discloses the highest emissions from the certification fleet for that engine family for which approval has been granted by the Board.

The following are the recommended values to be listed on the decal:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	gms/mi	gms/mi	gms/mi
1	1.7	19	2.2

These values are in effect until January 30, 1973. After this date, the exhaust emissions for each vehicle determined by factory assembly-line tests in accordance with the "Assembly-Line Test Procedure for 1973 and Subsequent Model Light-Duty Vehicles" must be shown on a decal.

Section 3 of the above procedure requires the manufacturer to submit, before the start of a model-year, a list of the items to be functionally checked and the procedure, including instrumentation, for performing these checks.

In accordance with Section III E. of the California Exhaust Emission Standards and Test Procedures for 1973 through 1976 Models Gasoline-Powered Light-Duty Motor Vehicles, the manufacturer is required to inform the ARB of any production changes which will affect emissions.

DAIMLER-BENZ, AG.

EXECUTIVE ORDER A-3-1

Supplemental information sheets are attached to this Order which include tune-up specifications and emission control system data.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair of the Department of Consumer Affairs will be notified of this approval by copy of this Order and attachment.

Executed at Sacramento, California, this 18th day of September, 1972.

JOHN A. MAGA Executive Officer

SUPPLEMENTAL INFORMATION Light Duty Vehicles 1973 Model-Year AIR RESOUR **DEVO**

MANUPACTURER: DAIMLER-BENZ (MERCEDES)

1		l I]_
		Ħ	H	*	MANUFACTURER:
		нв 280 (нв 280с	нв 220	Mode1	CTURE
		MB 280 & MB 280C	 		
		167.5	134	Engine C.I.D.	DAIMLER-BENZ
	•			Carl No.o	1
1.		4	س	Carburetor No.of Venturi	(MERCEDES)
Vacuum s		>	& &	Trans-	
switch controls			Bosch To be supplied	Distributo Make & No.	
				Distributor Make & No.	
ECR			% A & C,	Type Adv.*	
		·	DVG	Carbu	
-			DVG - Solex To Be supplied	Carburetor	
•			2	Exhaust	EXECUTI
			ECIL	Emission Co	EXECUTIVE ORDER A-3-1
			rankcase Storage	Control System	1-3-1
	·		1,2,3,4	Other	

* C - Centrifugal

V - Vacuum

VR - Vacuum retard

Throttle valve lifter during deceleration.

Engine speed relay water temperature switch controls ignition retard.

Transmission controlled idle speed (with

automatic transmission)

AIR RESOURCES BOARD SUPPLEMENTAL INFORMATION 1973 Model-Year Light Duty Vehicles

MANUTACTURER: DAIMARR-BENZ (MERCEDES) DATE DAIMARR-BENZ (MERCEDES) DAIMARR-BENZ (MERCEDES) DAIMARR-BENZ (MERCEDES) DAIMARR-BENZ (MERCEDES) DAIMARR-BENZ (MERCEDES) DAIMARR DAIMA				7
(MERCEDES) Companies Comp	MB 280,	MB 220	Vehicle Model	MANUPACTURER:
(MERCEDES) Companies Comp	167-5	134	Engine C.I.D.	DA IMLER-
Trans- Engine Family Inertia Inertia Idle RPH Engine Height: Idle RPH Idle RPH Inertia Idle RPH Idle RPH Inertia Idle RPH			Carburetor No. of Venturi	1
Inertia Tune-up Specification Height Idle RPM Basic Timing	>	> X &	Trans- mission	
Inertia Tune-up Specification Idle RPH Basic Timing 3500 750 - 850 In neutral (@ 800 RPH) 3500 750 - 950 (@ 800 RPH) (@ 800 RPH)	п	H	Engine Family	wight waty ve
EXECUTIVE ORDER Tune-up Specification Basic Timing 10° BTDC @ 800 RPM 4° ATDC @ 800 RPM	3500	3500	Inertia Weight	
EXECUTIVE ORDER A-3-1	750 - 950	750 - 850 in neutral	Tune	
Idle 60 or AFR 1.5 to 2.5% less than 1.5%	4° AIDC	10° BTDC	Basic Timing	EXECUTIVE ORDER
	less than 1.5%	1.5 to 2.5%	Idle CO or AFR	A-3-1