

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-5  
Relating to Approval of New Motor Vehicles

TOYO KOGYO CO. LTD.

Pursuant to the authority vested in the Air Resources Board by Sections 39150 and 39151 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Section 39023 of the Health and Safety Code and Executive Order G-45-1;

IT IS ORDERED AND RESOLVED: That Toyo Kogyo Co. Ltd. exhaust emission control systems for 1975 model-year passenger cars are approved for the engine family described below:

Engine Family: CNA  
Engine: 96.8 CID  
Exhaust Emission Control Systems: Air injection, thermal reactor

Models: Mazda 808 Sedan  
Mazda 808 Coupe  
Mazda 808 Station Wagon


The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1975 model vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
CNA	0.7	6.1	1.0

Vehicles approved under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 27 day of January, 1975.



G. C. Hass, Chief  
Division of Vehicle Emissions Control

AIR RESOL JS BOARD  
SUPPLEMENTAL INFORMATION  
1975 MODEL YEAR

PASSENGER CARS       LIGHT-DUTY TRUCKS

MANUFACTURER: TOYO KOGYO CO LTD.

EXECUTIVE ORDER NO. A-16-5

PAGE NO. 1

Engine Family	Vehicle Models (If coded see attachment)	Engine CID	Trans.	Inertia Weight	Distributor		Fuel System		Emission Control System		Tune-up Specifications			
					Type	Mfgr. Part No.	Type	Mfgr. Part No.	Type	OC <input type="checkbox"/> TR <input checked="" type="checkbox"/>	EGR Part No.	Idle RPM	Basic Timing	Idle Mixture
CMA	MAZDA 808 Sedan Coupe St. Wagon	96.8	H-4	2500	C	HITSURISHI T3T04372	1-2V	HITACHI DCJ328-1	AI & TR	361320800		800 +50 -0 in neutral	5°+ 1° BTDC at idle speed	2.0±0.5%

Abbreviations:

- |                         |                                       |
|-------------------------|---------------------------------------|
| Distributor             | Exhaust Emission Control System       |
| C - Centrifugal Advance | AI - Air Injection                    |
| V - Vacuum Advance      | EFI - Electronic Fuel Injection       |
| VR - Vacuum Retard      | EGR - Exhaust Gas Recirculation       |
|                         | EM - Engine Modifications             |
|                         | FI - Fuel Injection                   |
|                         | OC - Oxidation Catalyst               |
|                         | RC - Reduction Catalyst               |
|                         | TR - Thermal Reactor                  |
|                         | Evaporative Control System            |
|                         | CAN - Charcoal Canister Storage       |
|                         | TS - Tank Storage                     |
|                         | *Service                              |
|                         | I - Inspect, repair/replace as needed |
|                         | R - Replace                           |