State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-11-5 Relating to Certification of New Motor Vehicles

REGIE RENAULT

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That Regie Renault exhaust emission control systems for 1977 model-year passenger cars are certified for the engine family described below:

Engine Family: 843RC

Engine: 100.5 CID

Transmission: 3 Speed Automatic or 4 Speed Manual

Exhaust Emission Control Systems: Air Injection, Exhaust Gas

Recirculation, Oxidation Catalyst

Models: Renault 12GTL

Renault 12 Station Wagon

Renault 17 GTL

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1977 model-year vehicles:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	Grams per Mile	Grams per Mile	Grams per Mile
843RC	0.35	5.8	1.3

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this _____ day of May, 1977.

G. C. Hass, Chief

Vehicle Emissions Control Division

Manufacturer RENAULT Engine Family 843 RC		Executive Order No. A-]]-5 Page] Engine Engine (CID) 100.5 Code 843 RMC, RAC				
					Code <u>843 RMC, RAC</u>	
Emission Co	ntrol S	ys te m	AI, EGR, OC		+10%(A/C) Yes NoX
/ehicle Models (If Coded see attachment) RENAULT		Inertia Weight	Type C,V Mfgr.	Fuel System Type 1-2V Mfgr. Part Number	Part No.	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
12 GTL Sedan	A-3 M-4	2500	Ducellier #4546	Weber A-3 5601 M-4 5201	Guiot 15139B * I-25,000	(1) 7° BTDC @ 650 RPM (A- 7° BTDC @ 850 RPM (M- with disconnected vacuum advance. Eng. run at idle.
12 Station Wagon	A-3 M-4	2750 2500				(2) 3% + 1/-2; 650 RPM in drive (A-3) 800 RPM in neutra:(M-4 Disconnect air injection system.
17 GTL Coupe Conv.	A-3	2750				(3) 650 ± 50 RPM in drive (A-3) 850 ± 50 RPM in neutral (M-4) Air injection connecte
			ngine code 8 ngine code 8			

Abbreviations
Distributor
C-Centrifugal Advance
V-Vacuum Advance
VR-Vacuum Retard
HEI-High Energy Ignition
EI-Electronic Ignition
Fuel System
EFI, FI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emission Control System
AI-Air Injection
CAI-Catalyst Air Injection
EFL-Electronic Fuel Injection
EGR-Exhaust Gas Recirculation
EM-Engine Modification
EFE-Early Fuel Evaporation
ESAC-Electronic Spark Advance
Control
FI-Fuel Injection

OC-Oxidation Catalyst
PAI-Pulse Air Injection
RC-Reduction Catalyst
TR-Thermal Reactor
TWC-Three Way Catalyst
λ-Air Fuel Ratio Sensor
*Service
I-Inspect, repair/replace
as needed
R-Replace