Eo took

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-112 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Ford Motor Company exhaust emission control systems for 1978 model-year light duty trucks are certified for the vehicles described below:

Engine Family: 351W "A" (1X100)

Engine: 351 - CID
Transmission: 3-speed Automatic

Exhaust Emission Control Systems: Air Injection, Exhaust Gas

Recirculation, Oxidation Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	Grams per Mile	Grams per Mile	Grams per Mile
351W "A" (1X100)	0.7	6	1.7

BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-10 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this _____ day of August, 1977.

G. C. Hass, Chief

Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Ford Motor Company Executive Order No. A-10-112 Page 1

Engine Family 351W "A" (1X100) Engine (CID) 351

ABBREVIATIONS

<u>Distributor</u>
C-Centrifugal Advance
V-Vacuum Advance
VR-Vacuum Retard
HEI-High Energy Ignition
EI-Electronic Ignition
Fuel System
EFI, FI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System
AI-Air Injection
CAI-Catalyst Air Injection
CAB-Chamber Air Bleed
DD-Dual Displacement
EFI-Electronic Fuel Injection
EGR-Exhaust Gas Recirculation
EM-Engine Modification
EFE-Early Fuel Evaporation
ESAC-Electronic Spark Advance
Control
FI-Fuel Injection

OC-Oxidation Catalyst
PAI-Pulse Air Injection
RC-Reduction Catalyst
TC-Turbo Charged
TR-Thermal Reactor
TWC-Three Way Catalyst
 (Feedback Control)
EGR Syst. Service
I-Inspect, repair/replace
As needed
R-Replace

Model	Body <u>Type</u>	Wheelbase	Box <u>Design</u>	Trim <u>Levels</u>
E-100	Regular Van Club Wagon	SWB or LWB SWB	A,B, or C	1,2,3 1,2,3,

<u>Wheelbase</u>	Box Design	Trim Level
SWB Short Wheelbase LWB Long Wheelbase	A. Cargo Van B. Display Van C. Window Van	 Standard Custom Custom

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Control Sys	stem _	Inertia Weight Class	Distributor Type c, v Mfgr. Part Number Ford D7UE-	Fuel System	Part No. Service**	Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed (1) 10° BTDC + 2° @ 50° RPM in neutral W/ vacuum line disconnected and plugged at distributor (2) Preset at factory. Do not adjust. See
le Models oded see chment)	Trans	Inertia Weight Class RLHP	Distributor Type c, v Mfgr. Part Number Ford D7UE-	Fuel System Type 2 V Mfgr. Part Number Ford D8UE-	EGR System Part No. Service** D8UE- 9D448-GA	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed (1) 10° BTDC + 2° @ 50° RFM in neutral W/ vacuum line disconnected and plugged at distributor (2) Preset at factory. Do not adjust. See
oded see chment)	Trans	Weight Class RLHP	Type c, v Mfgr. Part Number Ford D7UE-	Type 2 v Mfgr. Part Number Ford D8UE-	Part No. Service** D8UE- 9D448-GA	Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed (1) 10° BTDC + 2° @ 50° RPM in neutral W/ vacuum line disconnected and plugged at distributor (2) Preset at factory. Do not adjust. See
LWB	A-3	4500	Ford D7UE-	Ford D8UE-	D8UE- 9D448-GA	(3) Idle Speed (1) 10° BTDC + 2° @ 50° RPM in neutral W/ vacuum line disconnected and plugged at distributor (2) Preset at factory. Do not adjust. See
LWB	A-3		D7UE-	DSUE-	D8UE- 9D448-GA	RPM in neutral W/ vacuum line disconnected and plugged at distributor (2) Preset at factory. Do not adjust. See
						(2) Preset at factory. Do not adjust. See
	i					Ford 1978 Service Manual.
						(3) 700 ± 50 RPM in drive. 500 ± 50 RPM in neutral with TSP Off. All hoses connected.
	All l for abbr	All mode	All models have	All models have special road	All models have special road load HP set	All models have special road load HP settings.

Date of Issue081877 Revisions: