State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-113 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Ford Motor Company exhaust emission control systems for 1978 model-year light duty trucks are certified for the vehicles described below:

Engine Family: 351M/400 "A" (1X100)

Engine: 351 CID

Transmission: 3-speed Automatic,

Exhaust Emission Control Systems: Air Injection, Exhaust Gas

Recirculation, Oxidation Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	Grams per Mile	Grams per Mile	Grams per Mile
351M/400 "A" (1X100)	0.8	12	1.2

BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-10 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this ______ day of August 1977.

S. C. Hass, Chief

Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer_	Ford Motor Company	_Executive Order No. A-10-113	Page1
Engine Family	351M/400 A (1X100)	Engine (CID) 351	

ABBREVIATIONS

<u>Distributor</u>
C-Centrifugal Advance
V-Vacuum Advance
VR-Vacuum Retard
HEI-High Energy Ignition
EI-Electronic Ignition
Fuel System
EFI, FI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System
AI-Air Injection
CAI-Catalyst Air Injection
CAB-Chamber Air Bleed
DD-Dual Displacement
EFI-Electronic Fuel Injection
EGR-Exhaust Gas Recirculation
EM-Engine Modification
EFE-Early Fuel Evaporation
ESAC-Electronic Spark Advance
Control
FI-Fuel Injection

Trim Level

Vehicle <u>Line</u>	Body <u>Type</u>	Whee I base	Box <u>Design</u>	Trim <u>Levels</u>
F-100	Regular Cab	SWB or LWB	A or B	1,2,3,4
	Super Cab	SWB or LwB	Α	1,2,3,4

Wheelbase

SWB Short Wheelbase LWB Long Wheelbase	A. Styleside B. Flareside	 Custom Ranger Ranger XLT Ranger Lariat

Box Design

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

	sion Control Sy	stem <u>F</u>	GR/AI/C)C/	Allowan	-10%(A/C)	Code 8-60s-R11 Yes ■ No□ included in RLHP
Eng. Code	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class RLHP	Mfor	Type 2 V	Part No	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	Regular Cab SWB, LWB	A-3	4500 20.5	Ford D7AE- 12127-BA	Ford D8TE- 9510-CRA	D80E- 9D448-BA	and plugged at
	Super Cab SWB, LWB						distributor.
							(2)Preset at factor Do not adjust. S 1978 Ford service manual.
				•			(3) 650±50 RPM in drive. All hoses connected

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

☐ Passe 	•		Light-Duty Executive		$\tau^{\alpha_{0}}$	
Engine Family 351M		 _	_		351	Engine Code 8-60s-R12
Emission Control S			The State of the S		+10%(A/C)	Yes 四 No□
Eng. Vehicle Models Code (If Coded see	Trans		Distributor Type C,V			
attachment)		RLHP	Mfgr. Part Number	Mfgr. Part Number	Part No Service**	(1) Basic Timing (2) Idle Mixture (3) Idle Speed
F-100 Regular Cab SWB, LWB	A-3	4500 20.5	Ford D7AE- 12127-BA	Ford D8TE- 9510-CRA	D80E- 9D448-BA	(1) 8° BTDC + 2° 500 RPM in neutral W/vaccum line disconnected and plugged at
Super Cab SWB, LWB						distributor.
						(2)Preset at factory Do not adjust. Se 1978 Ford service manual.
						(3) 650±50 RPM in drive. All hoses connected
-						

Date of Issue 11/15/77 Revisions: R/C-38T