State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-102 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Ford Motor Company exhaust emission control systems for 1978 model-year passenger cars are certified for the vehicles described below:

Engine Family: 2.3 "B" (ITS80X80) Engine: 140 CID Transmission: 3-speed Automatic, 4-speed Manual Exhaust Emission Control Systems: Air Injection, Exhaust Gas Recirculation, Three Way/Oxidation Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides		
	Grams per Mile	Grams per Mile	<u>Grams per Mile</u>		
2.3 "B" (1TS80X80)	0.39	- 3.8	0.9		

BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-10 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles". FORD MOTOR COMPANY

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

4

Executed at El Monte, California, this 12 day of August, 1977.

Rnast

G. C. Hass, Chief Vehicle Emissions Control Division

Manufacturer Ford Motor Company Executive Order No. <u>A-10-102</u> Page 1

Engine Family <u>2,3 "B" (1TS80x80)</u>Engine (CID) <u>140</u>

ABBREVIATIONS <u>Distributor</u> C-Centrifugal Advance V-Vacuum Advance VR-Vacuum Retard HEI-High Energy Ignition EI-Electronic Ignition <u>Fuel System</u> EFI, FI nV-nVenturi Carburetor VV-Variable Venturi

Exhaust Emissions Control System AI-Air Injection CAI-Catalyst Air Injection CAB-Chamber Air Bleed DD-Dual Displacement EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification EFE-Early Fuel Evaporation ESAC-Electronic Spark Advance Control FI-Fuel Injection

OC-Oxidation Catalyst PAI-Pulse Air Injection RC-Reduction Catalyst TC-Turbo Charged TR-Thermal Reactor TWC-Three Way Catalyst (Feedback Control) EGR Syst. Service I-Inspect, repair/replace as needed R-Replace

a'	Model	Body Type	Body <u>Code</u>	Model Name		
	Pinto	2-Door Sedan 3-Door Sedan Station Wagon	62B 64B 73B	Pinto/Pinto Pony Pinto Pinto/Pinto Squire		
	Bobcat	3-Door Sedan Station Wagon	64H 73H	Bobcat Bobcat/Bobcat Villager		

.

Eng	ufacturer Ford gine Family_2.3 "	Motor B" (ITS	Company 80 X 80) Engine	tive Order No e (CID)	A-10-102	2 Page 1 Engine Code 8-1P-RO
Eng	Ssion Control Sy Vehicle Models (If Coded see attachment)	Trans	Inertia	Distributor Type c, v Mfgr.	Fuel System Type 2 V	EGR System Part No.	
	Pinto Sedan 62B 64B Bobcat Sedan 64H	A-3	3000	Ford D7EE- 12127-CA	Holly W/Air Condition D8EE- 9510-HA WO/Air Condition	D7EE- 9D475-GA	(2) Preset at factory Do not adjust.
	Pinto Station Wagon 73B Bobcat Station Wagon 73H		3000		D8EE- 9510-EA		See 1978 Ford Service Manual (3) 750 <u>+</u> 50 RPM in drive with all hoses connected.
Col	mments: some e page for abbr ** No serv	eviati	ons and	special road model codes.	load HP set	tings.	

-	ne Family <u>2.3 "</u> sion Control Sys							
ing. Code	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class	Mfar.	Fuel System Type 2V Mfgr. Part Number	Part No.	Spec (1) (2)	-Up ification Basic Timing Idle Mixture Idle Speed
	Pinto Sedan 62B 64B Bobcat Sedan 64H	M-4	2750	Ford D7EE- 12127-EA	Holly W/Air Condition B885- 9510-GA WØ/Air Condition	D788- 9 D475-KA	(2)	6° BTDC <u>+</u> @ 650 RPM in neutral W/Vacuum line disconnected at distributor Preset at factory Do not adjust.
į	Pinto Station Wagon 73B Bobcat Station Wagon 73H		3000		D8EE- 9510-FA		(3)	See 1978 Ford Service Manual. 850 <u>+</u> 50 RPM in neutral with all hoses connected.
Com See	ents: some page for abbr ** No servi	eviati	ons and	special road model codes.	load HP set	tings.		

-	ne Family 2.3 " sion Control Sys		1. N. 1			140 +10%(A/C)	Code <u>8-2T-RO</u> Yes □ No KG
	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class	Mfgr.	Туре 2 у	Part No.	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	Pinto Sedan 62B 64B Bobcat Sedan 64H	M-4	2750	Ford D7EE- 12127-EA	Holley W/Air Condition D8EE- 951Q-ANA	D7EE- 9D475-LA	(1) 6 ⁰ BTDC <u>+</u> 2 ⁰ @ 650 RPM in neutral W/Vacuum line disconnected at distributor
			-		WO/Air Condition D8EE- 9510-AMA		<pre>(2) Preset at factory. Do not adjust. See 1978 Ford Service Manual (3) 850 + 50 RPM in</pre>
							neutral with all hoses connected.
Comm See	ents: some page 1 for abbr ** No serv	eviati	ons and	special road model codes.	load HP set	tings.	

L

		🖬 Passen	ger Car	rs 🗆] Light-Duty	Trucks 🛛	Medium Duty	/ Vehicles	
	Manut	facturer Ford	Motor	Company	Execut	tive Order No	A-10-102	Page 4 Engine	
	Engir	e Family 2.3 "	B" (175	5 80 x 80)) Engine	e (CID)	140	Code 8-1P-RI	
	Emis	sion Control Sys	stem <u>1</u>	GR, AI,	OC, TWC		10%(A/C)	Yes 🔲 No 🖾	
	Eng. Code	Vehicle Models (If Coded see attachment)	Trans	Weight Class	Type c, v Mfar.	Fuel System Type 2 V Mfgr. Part Number	Part No.	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed	
		Pinto Sedan 62B 64B Bobcat Sedan	A-3	3000	Ford D7EE- 12127-CA	Holly W/Air Condition D8EE- 9510-HA WO/Air Condition D8EE- 9510-EA	D7EE- 9D475-GA	 (1) 17 BTDC + @ 600 RPM in neutral W/Vacuum line disconnected at distributor (2) Preset at factory. Do not adjust. See 1978 Ford Service Manual 	
		64H Pinto	•	3000					
		Station Wagon 73B Bobcat Station Wagon						(3) 750 ± 50 RPM in drive with all hoses connected.	
		73H							
								•	
	See	ents: some page for abbr ** No serv of Issue 08127 R/C	reviati vice re 17 Re	ons and quired	special road model codes. 10/24/77 1		tings.		
	4	, •							