

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-17-39
Relating to Certification of New Motor Vehicles

AMERICAN MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That American Motors Corporation exhaust emission control systems for 1978 model-year passenger cars are certified for the vehicles described below:

- Engine Family: I-C
- Engine: 258 CID
- Transmission: 3-Speed Automatic and 4-Speed Manual
- Exhaust Emission Control Systems: Air Injection, Exhaust Gas Recirculation, Oxidation Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
I-C	0.28	3.5	1.4

BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-17 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 2 day of September, 1977.



G. C. Hass, Chief
Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer American Motors Corp. Executive Order No. A-17-39 Page 1

Engine Family I-C Engine (CID) 258

ABBREVIATIONS

Distributor

C-Centrifugal Advance

V-Vacuum Advance

VR-Vacuum Retard

HEI-High Energy Ignition

EI-Electronic Ignition

Fuel System

EFI, FI

nV-nVenturi Carburetor

VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection

CAI-Catalyst Air Injection

CAB-Chamber Air Bleed

DD-Dual Displacement

EFI-Electronic Fuel Injection

EGR-Exhaust Gas Recirculation

EM-Engine Modification

EFE-Early Fuel Evaporation

ESAC-Electronic Spark Advance
Control

FI-Fuel Injection

OC-Oxidation Catalyst

PAI-Pulse Air Injection

RC-Reduction Catalyst

TC-Turbo Charged

TR-Thermal Reactor

TWC-Three Way Catalyst
(Feedback Control)

EGR Syst. Service

I-Inspect, repair/replace
as needed

R-Replace

Vehicle Model

Pacer Sedan

Pacer Wagon

Concord Wagon

Concord 4-door

Concord 2-door

Concord Hatchback

Gremlin

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars Light-Duty Trucks Medium Duty Vehicles

Manufacturer American Motors Corp. Executive Order No. A-17-39 Page 1A

Engine Family I-C Engine (CID) 258 Engine Code see below

Emission Control System AI, EGR, OC +10%(A/C) Yes No

Eng. Code	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class	Distributor Type EI, V, C Mfgr. Part Number	Fuel System Type I-IV Mfgr. Part Number	EGR System Part No. Service	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
KMC-3D	Grenlin Concord Wagon Hatchback 2-door 4-door	M-4	3500	Motorcraft D8FE-12127-EA AM Part # 3232434	Carter 7235 AM Part # SF-3231191	3230176 I-30,000 mi.	(1) 6°+2° BTDC @ 850 RPM in neutral with engine at normal operating temperature, air cleaner on, air conditioning off and vacuum line off and plugged.
KMC-3D-1	Pacer Sedan Wagon					3230839	(2) 50 RPM lean drop. (3) 850+100 RPM in neutral
KAC-3D		A-3			Carter 7201 AM Port # SF 3231190	3230181 I-30,000 mi.	(1) 8°+2° BTDC @ 700 RPM in drive with engine at normal operating temperature, air cleaner on, air conditioning off and vacuum line off and plugged.
KAC-3D-1					Carter 7318	3230261	(2) 25 RPM lean drop. (3) 700+100 RPM in drive

Comments: _____ models have special road load HP settings.
See page 1 for abbreviations and model codes.

Engine code KAC-3D-1 per running change 78-27

Date of Issue _____ Revisions: _____

Engine code KMC-3D-1 added per running change No. 78-39.