

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-26
Relating to Certification of New Motor Vehicles

DAIMLER-BENZ AKTIENGESELLSCHAFT

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Daimler-Benz Aktiengesellschaft exhaust emission control systems for 1978 model-year passenger cars are certified for the vehicles described below:

Engine Family: 78/2B/L6E/28
Engine: 167.5 CID
Transmission: 4-Speed Automatic
Exhaust Emission Control Systems: Air Injection, Fuel Injection, Exhaust Gas Recirculation, Oxidation Catalyst, Reduction Catalyst

Models and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
78/2B/L6E/28	0.32	1.9	1.3

BE IT FURTHER RESOLVED: That the above models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-3 series.

BE IT FURTHER RESOLVED: That the above models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

DAIMLER-BENZ AKTIENGESELLSCHAFT

EXECUTIVE ORDER A-3-26
(Page 2 of 2)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 28 day of October, 1977.



G. C. Hass, Chief
Vehicle Emissions Control Division

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Daimler-Benz AG Executive Order No. A-3-26 Page 1

Engine Family 78/2B/L6E/28 Engine (CID) 167.5

ABBREVIATIONS

Distributor

C-Centrifugal Advance

V-Vacuum Advance

VR-Vacuum Retard

HEI-High Energy Ignition

EI-Electronic Ignition

Fuel System

EFI, FI

nV-nVenturi Carburetor

VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection

CAI-Catalyst Air Injection

CAB-Chamber Air Bleed

DD-Dual Displacement

EFI-Electronic Fuel Injection

EGR-Exhaust Gas Recirculation

EM-Engine Modification

EFE-Early Fuel Evaporation

ESAC-Electronic Spark Advance
Control

FI-Fuel Injection

OC-Oxidation Catalyst

PAI-Pulse Air Injection

RC-Reduction Catalyst

TC-Turbo Charged

TR-Thermal Reactor

TWC-Three Way Catalyst
(Feedback Control)

EGR Syst. Service

I-Inspect, repair/replace
as needed

R-Replace

Vehicle Model

Mercedes-Benz

280 E

280 SE

280 CE

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars Light-Duty Trucks Medium Duty Vehicles

Manufacturer Daimler-Benz AG Executive Order No. A-3-26 Page 1A

Engine Family 78/2B/L6E/28 Engine (CID) 167.5 Engine Code M 110 B

Emission Control System AI, EGR, FI, OC, EC +10%(A/C) Yes No

Eng. Code	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class	Distributor Type C, V, VR, EI Mfgr. Part Number	Fuel System Type FI Mfgr. Part Number	EGR System Part No. Service	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	Mercedes-Benz 280 E 280 SE 280 CE	A-4	4000	Bosch 0 237 304 003 MB Part # 002 158 5201	Bosch 0 438 120 032 0 438 100 011 MB Part # 000 070 0806	PE 20 338 MB Part # 000 140 5860 No Service	(1) TDC at idle, vacuum connected. (2) 0.4 - 2.0% air injection dis- connected; trans- mission in neutral, accessories not in operation (measured at exhaust manifold tap cyl. 1-3, dis- connect hose to EGR transducer) (3) 800 RPM with air injection dis- connected, trans- mission in neutral and AC in "off" position.

Comments: models have special road load HP settings.
See page 1 for abbreviations and model codes.

Date of Issue Revisions: