State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-155 Relating to Certification of New Motor Vehicles

LUXTRANS INDUSTRIES

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Luxtrans Industries exhaust emission control systems for 1978 model-year light-duty trucks are certified for the vehicles described below:

Engine Family: 20R(TC)
Displacement: 133.6 CID

Exhaust Emission Control Systems: Air Injection, Exhaust Gas

Recirculation, Oxidation Catalyst

Models, Transmissions and Engine Codes as listed in attachment.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1978 model-year vehicles:

Engine Family	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per Mile	* *	Nitrogen Oxides Grams per Mile
20R(TC)	0.2	9		1.7

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (13 California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-155 series.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-powered Motor Vehicles except Motorcycles".

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this ______ day of April 1978.

G. C. Hass, Chief

Vehicle Emissions Control Division

8. C IKNAN

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Luxtrans Industranc. Inc. Engine Family 20R (TC)		to. <u>A-155</u> 33.6	Page1	•
ABBREVIATIONS Distributor C-Centrifugal Advance V-Vacuum Advance VR-Vacuum Retard HEI-High Energy Ignition EI-Electronic Ignition Fuel System EFI, FI nV-nVenturi Carburetor VV-Variable Venturi	Exhaust Emissions Con AI-Air Injection CAI-Catalyst Air Inje CAB-Chamber Air Bleed DD-Dual Displacement EFI-Electronic Fuel 1 EGR-Exhaust Gas Recin EM-Engine Modification EFE-Early Fuel Evapor ESAC-Electronic Spark Control FI-Fuel Injection	njection culation n ation Advance	OC-Oxidation Cataly PAI-Pulse Air Inject RC-Reduction Cataly TC-Turbo Charged TR-Thermal Reactor TWC-Three Way Catal	ction yst lyst rol)
Engine Code	Model _	Transmission	<u>1</u>	

0dyssey

CM-CT

1978 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

	□ Passen	ger Ca	rs D	☑ Light-Duty	Trucks	Medium Dut	y Vehicles
Man u	facturer <u>Luxtra</u>	ns Ind	<u>ustries</u>	Execu	tive Order No	A-155	Page2
Engir	ne Family 2	OR (TC) (Toyota	a) Engine	e (CID)	133.6	Engine Code
Emiss	sion Control Sy	stem _	AI, EG	R, OC	<u> </u>	+10%(A/C)	Yes 🗆 No 🖸
	Vehicle Models (If Coded see attachment)	Trans	Inertia Weight Class	Distributor Type	Fuel System Type	EGR System	Tune-Up Specification
					Mfgr. Part Number		(1) Basic Timing(2) Idle Mixture(3) Idle Speed
CM-CT	Odyssey	4M	4000	19100-38060	21100-38161		1) 8° BTDC @ Idle.
						38121	2) Lean drop idle.
			:				3) 800 RPM
			:				Lean Drop Method
							Set to the following value at best idle • 870M, 920A, RPM turn idle mixture adjusting screw until 800M, 850A.
				:			
Comme See p	ents: page I for abbro				load HP sett (38.35 Sq.	_	3 = 22H.P.)
Date	of Issue	Rev	/isions:				
		070					

April 1, 1978