State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-164 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Ford Motor Company exhaust emission control systems for 1979 model-year gasoline-powered light duty trucks are certified for the vehicles described below:

Engine Family	Displacement Cubic Inches	Exhaust Emission Control Systems (Special Features)
5.8M/6.6"B" (1X128)	351/400	Exhaust Gas Recirculation, Air Injection, Oxidation Catalyst

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

Family Engine	.Inertia .Weight .Class	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile
5.8M/6.6"B" (1X128)	4500	0.30	3.5	1.5

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-10 series.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2/day of July, 1978.

J. L. TMM G. C. Hass, Chief

Yehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer	Ford Mo	tor Co.	Executive	Order	No.	A-10- 164	Page	
Engine Famil	y 5.8M/6. 6	6 "B" (1X	128) Engine (C	ID)		351		

ABBREVIATIONS
Ignition System
CA-Centrifugal Advance
EI-Electronic Ignition
ESAC
VA-Vacuum Advance
VR-Vacuum Retard

Fuel System
EFI, MFI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System AI-Air Injection CCAV-Comb. Chamber Air Valve EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification

ESAC-Electronic Spark Advance Control MFI-Mechanical Fuel Injection

Vehicle Model	Body <u>Type</u>	Wheelbase	Box Design	Trim Levels
F-100	Regular Cab	SWB or LWB	A or B	1, 2, 3, 4
	Regular Cab Chassis Cab	SWB or LWB	-	1, 2, 3, 4
	Super Cab	SWB or LWB	A	1, 2, 3, 4
	Super Cab Chassis Cab	SWB or LWB	-	1, 2, 3, 4

Evaporative Family: TN, TD

Date of issue

Revisions

1070	ATR	RESOURCES	ROARD	SUPPLEMENTAL	ΠΔΤΔ	SHEET
12/2	L L L L	VEDUDICED	טטאאטט	JULFELFILMINE	תותע	JIILLI

	Passeng	er Cars	x	Light-Duty	y Trucks	Medium-Duty	Veh	nicles
	anufacturer				•	51	Eng	ge <u>2</u> gine 9-60s-RON de** 9-60s-ROA
	mission Control					0% (A/C)	Yes	x No
	Vehicle Models (If Coded see attachment)	Trans.	Inertia Weight Class	Ign. Sys.	Fuel System 2 V Part Number		(1) (2)	ne-up ecification Basic Timing Idle Mixture Idle Speed
•	Regular Cab SWB, LWB Cab & Chassis Regular Cab SWB, LWB Super Cab SWB, LWB Cab & Chassis Super Cab SWB, LWB	A-3	4500	Ford D9TE- 12127-AJA	Ford W/AC D9TE- 9510-BRA WO/AC D9TE- 9510-BPA W/AC D9TE- 9510-BRB WO/AC D9TE- 9510-BPB	9D448-DA	(2)	10° BTDC @ 500 RPM in neutral W/Vacuum line disconnected & plugged at distributor. Preset at factory Do not adjust. See 1979 Ford Service Manual. 550 ± 50 RPM in drive. All hoses connected.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

**Engine Code Letter Suffix (Air Condition): A - A/C, N - Non A/C, B - Both A/C & Non A/C

Date of Issue - 073178 Revisions (1) R/C-104, add carb. P/N, 083078

1070	ΔTD	RESOURCES	ROARD	SUPPLEMENTAL	ΠΔΤΔ	SHEFT
19/9	AIK	KE SUUKUES	DUAKU	SUPPLEMENTAL	UHIH	SHELL

	Passeng	er Cars	X]Light-Du	ıty Trucks [Medium-Duty	Vehicles
M	anufacturer	Ford 1	lotor Co	mpany			_ Page3
E	ngine Family 5.	8M/6.6"B	'(1x128)	Enç	gine (CID)	351	Engine 9-60s-R10N Code** 9-60s-R10A
Eı	mission Control	System _	EGR, AI,	OC	+ '	10% (A/C)	Yes <u>X</u> No
	Vehicle Models (If Coded see attachment)	Trans.		CA, VA	5. Fuel System 2 V Der Part Number		Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	Regular Cab SWB LWB Cab & Chassis Regular Cab SWB LWB Super Cab SWB LWB Cab & Chassis Super Cab SWB LWB	A-3	4500	Ford D9TE- 12127-AJ	Ford W/AC D9TE- 9510-DGA WO/AC D9TE- 9510-DFA W/AC D9TE- 9510 DGB WO/AC D9TE- 9510-DFB	9D448-DA	(1) 10° BTDC @ 500 RPM in neutral W/Vacuum line disconnected & plugged at distributor. (2) Preset at factory. Do not adjust See 1979 Ford Service Manual. (3) 550 ± 50 RPM in drive. All hoses connected.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

**Engine Code Letter Suffix (Air Condition): A - A/C, N - Non A/C, B - Both A/C & Non A/C

Date of Issue -100278 Revisions 5.8M/6.6-117