## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-10-144 • Relating to Certification of New Motor Vehicles

## FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4:

IT IS ORDERED AND RESOLVED: That Ford Motor Company exhaust emission control systems for 1979 model-year gasoline-powered passenger cars are certified for the vehicles described below:

Engine Family	Displacement Cubic Inches	Exhaust Emission Control Systems (Special Features)
2.8"BV"(1x150)	171	Exhaust Gas Recirculation, Air Injection, Oxidation Catalyst

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

Family Engine	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	Grams per Mile	Grams per Mile	Grams per Mile
2.8"BV"(1x150)	0.36	7.4	1.3

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-10 series.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2 day of July, 1978.

G. C. Hass, Chief Vehicle Emissions Control Division

1070	ATD	PESOURCES	ROARD	SUPPLEMENTAL	DATA	SHEFT
19/9	AIK	KESOUKCES	DUMNU	SUFFEERENTAL	תוחש	JIILLI

•	ļ	JIJ MIN	KEJOOKCE	ווטכ שאאטע נ	CEMENTAL DATA		
	<b>X</b> Passeng	er Cars		Light-Duty	/ Trucks	Medium-Duty	Vehicles
	anufacturer	Ford M	lotor Co	mpany			Page 2 a Engine
E	ngine Family <u>2</u>	.8 иВУп	(1 x 150)	Engir	ne (CID)	171	Code 9-4N-ROB
E	mission Control	System _	EGR, AI,	OC .	+ 1	0% (A/C)	Yes <u>X</u> No
Eng. Code	Vehicle Models (If Coded see attachment)	Trans.	Inertia Weight Class	Ign. Sys.	Fuel System 2 V V Part Number		Tune-up Specification  (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	MUSTANG  Sedan 66B 61R 66H 61H  CAPRI  Sedan 61D 61H	A-3	3000	Ford 79TF-12100 FA Bosch (1) D79TF- 12100-FA	9510-LB	79TF-9D448 AB	(1) 6° BTDC @ 600 RPM in neutral W/Vacuum line disconnected at distributor.  (2) Preset at factory. Do not adjust. See 1979 Ford Service Manual.  (3) 700 ± 50 RPM in drive. 600 ± 50 RPM in neutral W/TSP Off. All hoses connected.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

Date of Issue - 072178 Revisions (1) R/C 2.8-7, Added alternate distributor.111578

## 1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer	Ford h	Motor	Company	Executive	0rder	No.	A-10-144	Page	_1
Engine Family	2.8	יישעיי (	(1 <b>x</b> 150)	Engine (C)	ID)		171		

ABBREVIATIONS
Ignition System
CA-Centrifugal Advance
EI-Electronic Ignition
ESAC
VA-Vacuum Advance
VR-Vacuum Retard

Fuel System
EFI, MFI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System AI-Air Injection CCAV-Comb. Chamber Air Valve EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification

ESAC-Electronic Spark Advance Control MFI-Mechanical Fuel Injection 

Model_	Body <u>Type</u>	Body Type	Model Name
Pinto	2-Door Sedan	62B	Pinto
	4-Door Sedan	64B	Pinto, Pinto ESS, Rallye (1)
	Station Wagon	73B	Pinto, Pinto Squire
Bobcat	3-Door Sedan	64Н	Bobcat
	Station Wagon	73H	Bobcat/Bobcat Villager
Mustang	2-Door Sedan	66B	Mustang
	2-Door Sedan	66H	Mustang Ghia
	3-Door Sedan	61R	Mustang
	3-Door Sedan	61H	Mustang Ghia
Capri	3-Door Sedan	61D	Capri
	3-Door Sedan	61H	Capri/Capri Ghia/Capri R/S

Evaporative Family E-1

(1) Added model 5-2-79

F	n	, #A-	1	O.	144
ь.	v	, //	_	v	

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET	1979	AIR	<b>RESOURCES</b>	BOARD	SUPPLEMENTAL	DATA	SHEET
--	------	-----	------------------	-------	--------------	------	-------

	<b>X</b> Passeng	ger Cars		Light-Duty	y Trucks	Medium-Duty	Vehicles
	lanufacturer	Ford !	Motor Co	ompany		<del></del>	Page 2
E	ngine Family	2.8 "BV	" (1 X 15	O) Engi	ne (CID)	l	Engine Code <b>9-4N-ROB</b>
Ε	mission Control	System _	EGR, AI,	oc .	+ 1	0% (A/C)	Yes <u>X</u> No
	Vehicle Models (If Coded see attachment)	Trans.		Ign. Sys.	Fuel System 2V V Part Number		Tune-up Specification  (1) Basic Timing (2) Idle Mixture (3) Idle Speed
	PINTO Sedan 62B 64B Station Wagon 73B BOBCAT Sedan 64H Station Wagon 73H	A-3	3000	Bosch (1)	9510-LB D9ZE- 9510-LC	79TF-9D448-AB	(1) 6° BTDC @ 600 RPM in neutral W/Vacuum line disconnected at distributor.  (2) Preset at factory. Do not adjust. See 1979 Ford Service Manual.  (3) 700 ± 50 RPM in drive. 600 ± 50 RPM in neutral W/TSP Off. All hoses connected.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

Date of Issue - 072178 Revisions (1) R/C 2.8-7, Added alternate distributor 111578