State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-12-13 Relating to Certification of New Motor Vehicles

FIAT S.p.A.

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Fiat S.p.A exhaust emission control systems are certified as described below for 1979 model-year gasoline-powered passenger cars:

Engine Family	Displacement Cubic Inches	Exhaust Emission Control Systems (Special Features)			
132-AC	121.7	Air Injection Exhaust Gas Recirculation Oxidation Catalyst			

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

Engine Family		Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile	
132-AC	0.22	5.2	1.4	

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, The California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _______ day of November, 1978.

G. C. Hass, Chief

Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer <u>Fiat S.p.A.</u>	Executive Order No. A-12-13	Page1	
Engine Family 132-AC	Engine (CID)121.7		
ABBREVIATIONS Ignition System CA-Centrifugal Advance EI-Electronic Ignition ESAC VA-Vacuum Advance VR-Vacuum Retard Fuel System EFI, MFI nV-nVenturi Carburetor	Exhaust Emissions Control System AI-Air Injection CCAV-Comb. Chamber Air Valve EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification EEC-Electronic Engine Control ESAC-Electronic Spark Advance Control MFI-Mechanical Fuel Injection	OC-Oxidation Catalyst PAI-Pulse Air Injection TC-Turbo Charged TR-Thermal Reactor TWC-Three Way Catalyst (Feedback Control) WOC-Warm-up Oxidation Catalyst	
VV-Variable Venturi Vehicle Model	•		
Brava 2-door Co Brava 4-door So Brava Station N	edan		

Spider 2000

Lancia Beta 2000 Sedan Lancia Beta 2000 Coupe Lancia Beta 2000 HPE Lancia Zagato

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

X Passenger Cars Light-Duty Trucks Medium-Duty						Vehicles		
							Page	1B
Engine Family 132-AC Engine (CID) 121.7							Engine Code see	below
Er	mission Control	System <u>A</u>	I, EGR,	OC	+ 1	0% (A/C)	Yes	No X
Eng. Code	Vehicle Models (If Coded see attachment)	Trans.		Ign. Sys. Control Parameters CA, VA, EI		EGR Valve		c Timing Mixture
D33XA. 8V20. A2C.		A-3	2750	Marelli Type 805 P2	Weber 28/32 ADHA6/279	R3413	A 70 (2) 1 - CO m	easured.
D33YA. 8V2O. A2C	Brava Station Wagon				Weber 28/32 ADHA6/179		(3) 750	ailpipe. <u>+</u> 50 RPM rive.
D35XA. 8V20.					Weber 28/32 ADHA8/179			
D37XA. 7V24. A3C			3000	Marelli Type 774 P2. Bosch	Weber 30/32 DHTA4/279	R3409	adjustme	ations and nts at
D37YA. 7V24. A3C				Type JGFU4	Weber 30/32 DHTA4/179		normal operating temperature, choke open, air injection line pinched off in a section between check valve and tee.	
							vaive all	u tee.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

Date of Issue -

^{*}Axle ratio is that of medium duty certification vehicle.

E.O. #A 12 _ 13

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

X Passenger Cars Light-Duty Trucks Medium-Duty						Vehicles	
□ lanufacturer Fiat S.p.A.							Page 1A
Engine Family <u>132-AC</u> Engine (CID) <u>121.7</u>							Engine Code <u>see below</u>
Ei	mission Control	System _	AI, EG	R, OC	+ 1	0% (A/C)	Yes No _X
Eng. Code	Vehicle Models (If Coded see attachment)	Trans.	Inertia Weight Class (Axle Ratio)*	Ign. Sys. Control Parameters CA, VA, EI	Typo: 1 2V	EGR Valve	Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
D32XA. 8V2O. A1C		M5	2750	Marelli Type 805 P2	Weber 28/32 ADHA5/279	R3609	(1) 10 ± 1.5° BTDC @ 800 to 850 RPM in neutral (2) 1-2.5% CO.
D32YA. 8V2O. A1C					Weber 28/32 ADHA5/179		CO measured at tailpipe. (3) 850 + 50 RPM
D34XA. 8V20 A1	Spider 2000		2500		Weber 28/32 ADHA7/179		in neutral.
D36XA. 8V2O. A4C.	Lancia Beta 2000 Sedan Lancia Beta 2000 HPE		3000	Marelli Type 774 P2. Bosch Type JGFU4	Weber 30/32 DHTA 3/279	R3408	Engine tune-up specifications and adjustments at normal operating temperature, choke
D36YA. 7V23. A4C	Lancia Zagato				Weber 30/32 DHTA3/179		open, air injection line pinched off in a section between check valve and tee.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

*Axle ratio is that of medium duty certification vehicle.

Date of Issue -

E.C. 77-12-13

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

•	X Passeng	jer Cars		· Light-Dut	y Trucks	 Medium-Duty	Vehicles
M	Manufacturer	Fiat S.p	.A				Page 1C
₩ E	Ingine Family	Engine Code <u>see below</u>					
E	mission Control	Yes No _X					
Eng. Code	Vehicle Models (If Coded see attachment)	Trans.	(Axle	Control Parameters	Fuel System Type: 1-2V Mfgr. Part Number	EGR Valve	Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
D36XA. 7V23. A4C	Lancia Beta 2000 Coupe	M-5	2750	Marelli Type 774 P2. Bosch Type	Weber 30/32 DHTA3/279	R3408	(1) 10 <u>+</u> 1.5° BTDC @ 800 to 850 RPM in neutral.
D36YA. 7V23. A4C				JĞFU4	Weber 30/32 DHTA3/179		(2) 1 - 2.5% CO. CO measured at tail- pipe. (3)850 <u>+</u> 50 RPM in neutral.
D37XA. 7V24. A3C D37YA. 7V24.		A-3			Weber 30/32 DHTA4/279 Weber 30/32 DHTA4/179	R3409	(1) 10 + 1.5° BTDC @ 700 to 750 RPM in drive. (2) 1 - 2.5% CO. CO measured at tail- pipe. (3) 750 + 50 RPM in
A3C					anorative emis		drive. Engine tune-up specifications and adjustments at normal operating temperature, choke open, air injection line pinched off in a section between check valve and tee.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

*Axle ratio is that of medium duty certification vehicle.

Date of Issue -