

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-145
Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That General Motors Corporation exhaust emission control systems for 1979 model-year gasoline-powered passenger cars are certified for the vehicles described below:

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
960V0	425	Air Injection, Exhaust Gas Recirculation Oxidation Catalyst (Electronic Fuel Injection)

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
960V0	0.27	3.9	1.3


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year, or have been granted a temporary exemption from the aforementioned "Specifications" by Executive Order AA-6 series.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16 day of August, 1978.



G. C. Hass, Chief
Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer General Motors Corp. Executive Order No. A-6-145 Page 1

Engine Family 960V0 Engine (CID) 425

Evaporative Family 9B0-6

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance

EI-Electronic Ignition

ESAC

VA-Vacuum Advance

VR-Vacuum Retard

Fuel System

EFI, MFI

nV-nVenturi Carburetor

VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection

CCAV-Comb. Chamber Air Valve

EFI-Electronic Fuel Injection

EGR-Exhaust Gas Recirculation

EM-Engine Modification

ESAC-Electronic Spark Advance Control

MFI-Mechanical Fuel Injection

OC-Oxidation Catalyst

PAI-Pulse Air Injection

TC-Turbo Charged

TR-Thermal Reactor

TWC-Three Way Catalyst (Feedback Control)

WOC-Warm-up Oxidation Catalyst

Division	Basic Body	Trim	Body Type	
6				<u>Cadillac</u>
	C	D	47	Coupe deVille
	C	D	69	Sedan deVille
	C	B	69	Brougham

AIR RESOURCES BOARD 1979 SUPPLEMENTAL DATA SHEET - GM FORMAT

Passenger Cars

Manufacturer: GENERAL MOTORS CORPORATION Executive Order No. A-6-145

Pg. 2

Engine Family 960V0 Engine CID 425 Transm. A-3

Exhaust Emission Control System AI /EGR/OC +10% (A/C) Yes No

Eng. Code	Air Cond.	Ign. Syst. EI,CA,VA Distrib. Part No.	Fuel System EFI ECU Part No.	EGR Valve Part No.	Inertia Wt. Class	Divisions	Basic Body	Trim	Body Type	Trans- mission	Tune-up Label & Page No.	Rev. Notes
2	W	Delco Remy 1103335	Bendix 1612947	7044591	4500	6	C	D	47	A-3	MK 3	
						6	C	D	69			
					5000	6	C	B	69			

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP lists for correct dyno test HP settings based on model, equipment and inertia weight class.

Date of Issue: 081878 Revisions:

Manufacturer: General Motors Corporation

Executive Order No. A-6-145 Pg. 3

MK
 *960V0
 980.6
 7.0 LITRE

VEHICLE EMISSION CONTROL INFORMATION
 GENERAL MOTORS CORPORATION



CATALYST A.I.R. - E.G.R.
 LOW ALTITUDE CERTIFICATION

TIMING (DEG. B.T.D.C. @ R.P.M.)	18 @ 1400
SPARK PLUG GAP (INCHES)	.060
THROTTLE BODY SCREW (R.P.M.)	650

1. PLACE TRANSMISSION IN PARK AND BLOCK DRIVE WHEELS
2. DISCONNECT AND PLUG VACUUM LINE TO PARKING BRAKE RELEASE TO PREVENT AUTOMATIC RELEASE OF PARKING BRAKE WHEN SHIFTING TRANSMISSION IN STEP 7.
3. SET PARKING BRAKE
4. WITH ENGINE AT NORMAL OPERATING TEMPERATURE, AIR CLEANER OFF AND AIR CONDITIONER OFF, MAKE ENGINE ADJUSTMENTS AS FOLLOWS:
5. DISCONNECT AND PLUG DISTRIBUTOR VACUUM LINE
6. WITH TRANSMISSION IN "PARK" SET TIMING AT SPECIFIED R.P.M.
7. RECONNECT DISTRIBUTOR VACUUM LINE PLACE TRANSMISSION IN "DRIVE" AND ADJUST THROTTLE BODY SCREW TO SPECIFIED R.P.M.
8. RECONNECT PARKING BRAKE RELEASE LINE

ELECTRONIC FUEL INJECTION
 NO ADJUSTMENT PROVISIONS EXIST FOR IDLE FUEL MIXTURE



SEE SERVICE MANUAL AND MAINTENANCE SCHEDULE I FOR ADDITIONAL INFORMATION
 THIS VEHICLE CONFORMS TO U.S. EPA AND CALIFORNIA REGULATIONS APPLICABLE TO 1979 MODEL YEAR NEW PASSENGER CARS.

PART NO. 1616866

