8.0. Boot

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-62 Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Chrysler Corporation exhaust emission control systems for 1979 model-year gasoline-powered passenger cars are certified for the vehicles described below:

Engine Family	Displacement Cubic Inches	Exhaust Emission Control Systems (Special Features)		
9CD-225-1-UP	225	Air Injection Exhaust Gas Recirculation Oxidation Catalyst		

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

Engine Family	Hydrocarbons ngine Family Grams per Mile		Nitrogen Oxides Grams per Mile
9CD-225-1-UP	0.40	7.3	1.3

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2 day of July, 1978.

G. C. Hass, Chief

Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer _	Chrysler Corp.	Executive Order	No.	A-9-62	Page	1
Engine Family	9CD-225-1-UP	Engine (CID)	225			

ABBREVIATIONS

Ignition System
CA-Centrifugal Advance
EI-Electronic Ignition
ESAC
VA-Vacuum Advance
VR-Vacuum Retard

Fuel System
EFI, MFI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System AI-Air Injection CCAV-Comb. Chamber Air Valve EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification

ESAC-Electronic Spark Advance Control MFI-Mechanical Fuel Injection

Model	Make/Type
FH22 FM22 FP22 FH41 FM41 FP41 FH45	Chrysler Le Baron Chrysler Le Baron Chrysler Le Baron Medallion Chrysler Le Baron Medallion Chrysler Le Baron Town & Country
GH22 GM22 GP22 GH41 GM41 GP41 GH45	Dodge Diplomat Dodge Diplomat Dodge Diplomat Medallion Dodge Diplomat Dodge Diplomat Dodge Diplomat Dodge Diplomat Dodge Diplomat Dodge Diplomat
HL29 - HL41 <i>-</i> HL45	Plymouth Volare Custom, Volare Premier, Duster, Road Runner, Volare Plymouth Volare, Volare Custom, Volare Premier Plymouth Volare, Volare Premier
NL29 - NL41 - NL45	Dodge Aspen, Aspen Custom, Aspen Special Edition, R/T Dodge Aspen, Aspen Custom, Aspen Special Edition Dodge Aspen, Aspen Special Edition

Evaporative Emission Control Family: 9E-2

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

	χ Passeng	er Cars		Light-Dut	y Trucks	Medium-Duty	Vehicles
						Page 2	
Е	ngine Family <u>9C</u>)-225-1-U	IP	Engi	ne (CID) <u>225</u>		Engine Code <u>A-S-l</u>
Eı						Yes X No	
Eng. Code	Vehicle Models (If Coded see attachment)	Trans.	Inertia Weight Class (Axle Ratio)*	Ign. Sys. CA, VA Distri- butor	Fuel System 1V	EGR Valve	Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
A-S-2 A-S-1	HL29 HL41 NL29 NL41 FH22, 41 FM22, 41 FP22, 41 FH45 GH22, 41 GM22, 41 GP22, 41	A-3	3500 4000	4091101	4095951	4104013 4105013	(1) 8 + 2° BTC w/vac. adv. disconnected (2) Propane gain - enriched idle: 925 rpm. See service manual. Alternate method - 0.3+1.7 % CO. See Service manual.
Comme	GH45 HL45 NL45	ne for a	bbreviat	ions and ev	aporative emis		(3) Curb idle: 750 <u>+</u> 100 rpm dentification.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

*Axle ratio is that of medium duty certification vehicle.

Date of Issue - 7-18-78