

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-29
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR COMPANY, LTD.

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Toyota Motor Company, Ltd. exhaust emission control systems are certified as described below for 1980 model-year gasoline-powered passenger cars.

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
20R(C)	139 (133.6)	Air Injection Exhaust Gas Recirculation Oxidation Catalyst

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
20R(C)	0.18	6.8	1.0

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1980 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That Toyota Motor Company, Ltd. has provided to the Executive Officer all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3rd day of August, 1979.



K. D. Drachand, Acting Chief
Mobile Source Control Division

1980 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Toyota Executive Order No. A-14-29 Page 1
 Engine Family 20R(c) Engine (CID) ~~137~~ / 33.9

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
 EEC-Electronic Engine Control
 EI-Electronic Ignition
 ESAC-Electronic Spark Advance Control
 VA-Vacuum Advance
 VR-Vacuum Retard

Fuel System

EFI, MFI
 nV-nVenturi Carburetor
 VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection
 CL-Closed Loop
 EGR-Exhaust Gas Recirculation
 EM-Engine Modification
 OC-Oxidation Catalyst
 PAI-Pulse Air Injection
 TR-Thermal Reactor
 TWC-Three Way Catalyst

Special Features

CCAV-Combustion Chamber Air Valve
 EFI-Electronic Fuel Injection
 MFI-Mechanical Fuel Injection
 TC-Turbo Charged

Engine Code

1,2

3,4

Model

Celica Coupe
 Celica Liftback
 Corona Sedan
 Corona Liftback
 Corona Station Wagon

Celica Coupe
 Celica Liftback
 Corona Sedan
 Corona Liftback
 Corona Station Wagon

1980 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

 Passenger Cars Light-Duty Trucks Medium-Duty Vehicles Gas Diesel
Manufacturer Toyota Motor Co.Page 2Engine Family 20R(C)CID-Type 134, I-4Engine Code 1-4ECS (Special Features) AI, EGR, OC

+ 10% (A/C)


Yes X No

Engine Code	Vehicle Models (If Coded see attachment)	Trans.	Test Weight Class (Inertia)	Ign. System CA, VA, EI Distributor Part No.	Fuel System 2V Carburetor Part No.	EGR Valve Part No.	Label Ident.
1, 2	Celica Coupe Celica Liftback	5M		Nippondenso 19100-38220	Aisan Kogyo 21100-38331	25620- -38211	See Page 3
	Corona Sdn Corona Liftback Corona St. Wgn			19100-38250			
3, 4	Celica Coupe Celica Liftback	3A	3000 (3000)	19100-38220		25620 -38191	
	Corona Sdn Corona Liftback Corona St. Wgn.			19100-38250			

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

1980 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Toyota Motor Co. Ltd. Executive Order No. A-14-29 Page 3

VEHICLE EMISSION CONTROL INFORMATION																									
ENGINE FAMILY	20R(C)	133.6 CID																							
EVAP. FAMILY	EV-RC																								
EXHAUST EMISSION CONTROL SYSTEM		AI+EGR+CCo																							
<p>MAKE ALL ADJUSTMENTS WITH ENGINE AT NORMAL OPERATING TEMPERATURE, CHOKE FULL OPEN, AIR CLEANER INSTALLED AND AIR CONDITIONER OFF.</p> <p>ENGINE TUNE UP SPECIFICATIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 40%;">TRANSMISSION</th> <th style="width: 30%;">MANUAL</th> <th style="width: 30%;">AUTOMATIC</th> </tr> </thead> <tbody> <tr> <td>IDLE SPEED (RPM)</td> <td>800(N)</td> <td>850(N)</td> </tr> <tr> <td>IGNITION TIMING (°BTDC)</td> <td colspan="2">8° @ MAX. 950 RPM</td> </tr> <tr> <td>IDLE MIXTURE SETTING</td> <td colspan="2">IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE-UP NOT RECOMMENDED.</td> </tr> <tr> <td>FAST IDLE SPEED (RPM)</td> <td colspan="2">2400 WITH EGR AND VACUUM ADVANCE OFF</td> </tr> <tr> <td>THROTTLE POSITIONER SETTING SPEED (RPM)</td> <td colspan="2">1050</td> </tr> <tr> <td rowspan="2">VALVE CLEARANCE (IN.)</td> <td>INTAKE</td> <td>0.008 (0.20 mm)</td> </tr> <tr> <td>EXHAUST</td> <td>0.012 (0.30 mm)</td> </tr> </tbody> </table>			TRANSMISSION	MANUAL	AUTOMATIC	IDLE SPEED (RPM)	800(N)	850(N)	IGNITION TIMING (°BTDC)	8° @ MAX. 950 RPM		IDLE MIXTURE SETTING	IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE-UP NOT RECOMMENDED.		FAST IDLE SPEED (RPM)	2400 WITH EGR AND VACUUM ADVANCE OFF		THROTTLE POSITIONER SETTING SPEED (RPM)	1050		VALVE CLEARANCE (IN.)	INTAKE	0.008 (0.20 mm)	EXHAUST	0.012 (0.30 mm)
TRANSMISSION	MANUAL	AUTOMATIC																							
IDLE SPEED (RPM)	800(N)	850(N)																							
IGNITION TIMING (°BTDC)	8° @ MAX. 950 RPM																								
IDLE MIXTURE SETTING	IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE-UP NOT RECOMMENDED.																								
FAST IDLE SPEED (RPM)	2400 WITH EGR AND VACUUM ADVANCE OFF																								
THROTTLE POSITIONER SETTING SPEED (RPM)	1050																								
VALVE CLEARANCE (IN.)	INTAKE	0.008 (0.20 mm)																							
	EXHAUST	0.012 (0.30 mm)																							
 TOYOTA MOTOR CO., LTD.	<h2 style="margin: 0;">CATALYST</h2>																								
<p>THIS VEHICLE CONFORMS TO U.S. EPA AND STATE OF CALIFORNIA REGULATIONS APPLICABLE TO 1980 MODEL YEAR NEW MOTOR VEHICLES PROVIDED THAT THIS VEHICLE IS ONLY INTRODUCED INTO COMMERCE FOR SALE IN THE STATE OF CALIFORNIA. THIS VEHICLE HAS DEMONSTRATED COMPLIANCE AT ALTITUDE BELOW 4,000 FEET.</p>																									