

E.O.

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-14  
Relating to Certification of New Motor Vehicles

SAAB-SCANIA AKTIEBOLAG

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Saab-Scania Aktiebolag exhaust emission control systems are certified as described below for 1980 model-year gasoline-powered passenger cars.

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
BI20CA	121	Three Way Catalyst Closed Loop (Mechanical Fuel Injection)

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1980 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
BI20CA	0.16	3.1	0.5

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1980 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That Saab-Scania Aktiebolag has provided to the Executive Officer all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 12<sup>th</sup> day of October, 1979.

  
K. D. Drachand, Acting Chief  
Mobile Source Control Division

1980 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Saab-Scania Executive Order No. A-22-14 Page 1  
 Engine Family BI20CA Engine (CID) 121

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance  
 EEC-Electronic Engine Control  
 EI-Electronic Ignition  
 ESAC-Electronic Spark Advance Control  
 VA-Vacuum Advance  
 VR-Vacuum Retard

Fuel System

EFI, MFI  
 nV-nVenturi Carburetor  
 VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection  
 CL-Closed Loop  
 EGR-Exhaust Gas Recirculation  
 EM-Engine Modification  
 OC-Oxidation Catalyst  
 PAI-Pulse Air Injection  
 TR-Thermal Reactor  
 TWC-Three Way Catalyst

Special Features

CCAV-Combustion Chamber Air Valve  
 EFI-Electronic Fuel Injection  
 MFI-Mechanical Fuel Injection  
 TC-Turbo Charged

Engine Code

P11, P11-AC  
 P12, P12-AC

P11, P11-AC  
 P11S, P11S-AC  
 P12, P12-AC

P11, P11-AC  
 P12, P12-AC

P04, P04-AC

Model

900 GL Hatchback

900 EMS Hatchback

900 GLE Hatchback

99 GL Sedan

50 Book

1980 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars     Light-Duty Trucks     Medium-Duty Vehicles     Gas     Diesel

Manufacturer Saab-Scania

Page 2

Engine Family BI20CA

CID-Type 121-I4

Engine Code

ECS (Special Features) TWC-CL (MFI)

+ 10% (A/C)

Yes X No

Engine Code	Vehicle Models (If Coded see attachment)	Trans.	Test Weight Class (Inertia)	Ign. System CA,VA,EI Distributor Part No.	Fuel System MFI Part No.	EGR Valve Part No.	Label Ident.	
P04 P04-AC	99 GL Sedan	M4	(2750) 2875	Bosch 0237002023	Bosch Fuel Distri- butor 0438 100 032		See Page 3	
P12-AC	900 GLE Hatchback	A3	(3000) 3250		Air Flow Sensor 0438 120 073			
P11-AC		M4			Warm up Regulator 0438 140 032			
P11S-AC		M5 (1)						
P12, P12- AC	900 GLE Hatchback 900 GL Hatchback	A3	(3000) 3125					
P11 P11-AC		M4						
P12	900 EMS Hatchback	A3	(3000) 3000					
P11S, P11S- AC		M5						
P11, P11-AC		M4						

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

Date of Issue - 101279

Revisions: (1) R/C 1980-02, Add M5 Trans to 900 GLE 043080

1980 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Saab-Scania Executive Order No. A-22-14 Page 3

EMISSION CONTROL INFORMATION		VACUUM HOSE ROUTING
MANUFACTURER: SAAB-SCANIA AB, SWEDEN MODELS: SAAB 2.0 M (MANUAL) SAAB 2.0 IA (AUTOMATIC)		<p>A schematic diagram showing the vacuum hose routing for the engine. The diagram includes the following components and their connections:</p> <ul style="list-style-type: none"> <li><b>AUXILIARY AIR VALVE</b>: Connected to the <b>CRANKCASE VENTILATION</b> system.</li> <li><b>DISTRIBUTOR</b>: Connected to the <b>INLET MANIFOLD</b>.</li> <li><b>THROTTLE VALVE HOUSING</b>: Connected to the <b>INLET MANIFOLD</b>.</li> <li><b>PRESSURE IMPULSE CONTACT</b>: Connected to the <b>POWER BRAKE</b> system.</li> <li><b>CARBON FILTER</b>: Connected to the <b>INLET MANIFOLD</b>.</li> </ul>
ENGINE FAMILY: BI 20 CA ENGINE SIZE: 121.1 CU. IN.		
EXHAUST EMISSION CONTROL SYSTEM: MECHANICAL FUEL INJECTION, EXHAUST OXYGEN SENSOR SYSTEM WITH CATALYST AND DASH POT.		
IDLE SPEED: 875 ± 50 R.P.M. (TRANSMISSION IN NEUTRAL AND A/C OFF). CO LEVEL AT IDLE (OXYGEN SENSOR CABLE DISCONNECTED): 0.75-1.25%. WHEN ADJUSTMENT IS NECESSARY, SET TO 1.0%. (NOTE: CO-METER SAMPLE PICK-UP IS LOCATED IN ENGINE COMPARTMENT CLOSE TO EXH. MANIFOLD.)		
IGNITION TIMING: 20° B.T.D.C. AT 2000 R.P.M. (DISTR. VACUUM LINE DISCONNECTED AND PLUGGED, TRANSMISSION IN NEUTRAL.) ENGINE SPEED WHEN THE DASH POT IS IN CONTACT WITH THE THROTTLE LEVER: 2500 ± 100 R.P.M.		
VALVE CLEARANCE: INLET: 0.006 - 0.012 IN.    OUTLET: 0.014 - 0.020 IN. SPARK PLUG GAP: 0.024 - 0.028 IN.		
THIS VEHICLE CONFORMS TO U.S. EPA AND STATE OF CALIFORNIA REGULATIONS APPLICABLE TO 1980 MODEL YEAR NEW MOTOR VEHICLES.		
<b>SAAB-SCANIA</b>		93 27 917