State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-44 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR COMPANY, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-3, and G-45-4:

IT IS ORDERED AND RESOLVED: That 1982 model-year Toyota Motor Company, Ltd. exhaust emission control systems are certified as described below for gasoline-powered passenger cars.

| Engine Family | Displacement Cubic Inches (Liters) | Exhaust Emission Control Systems (Special Features) |
|---------------|---------------------------------------|--|
| CTY2.4V2ECCO | 144.4 (2.4) | Air Injection-Pump Exhaust Gas Recirculation Three Way Catalyst with Closed Loop |

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the emission standards for this engine family to be listed on the window decal required by California Assembly-Line Test Procedures for 1982 model-year vehicles:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides |
|----------------|-----------------|-----------------|
| Grams per Mile | Grams per Mile | Grams per Mile |
| 0.39 | 7.0 | 0.7 |

The following are the certification emission values for this engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides |
|----------------|-----------------|-----------------|
| Grams per Mile | Grams per Mile | Grams per Mile |
| 0.13 | 3.3 | 0.2 |

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed in El Monte, California this 29^{M} day of July, 1981.

K. D. Drachand, Chief

Mobile Source Control Division

1982 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

| Manufacturer _ | Toyota Motor Co. | Executive Order No. | A-14-44 | Page _ | 1 |
|----------------|------------------|----------------------|---------------|--------|---|
| Engine Family | CTY2.4V2ECCO | Evaporative Family _ | EV-R1 / EV-R2 | | |
| 4 | | Engine CID (Liters) | 144.4 (2.4) | | |

ABBREVIATIONS

Ignition System
CA-Centrifugal Advance
EEC-Electronic Engine Control
EI-Electronic Ignition
ESAC-Electronic Spark Advance
Control
VA-Vacuum Advance
VR-Vacuum Retard

Fuel System
CFI, CL, DID, DIP, EFI, MFI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System
AIP-Air Injection-Pump
AIV-Air Injection-Valve
CL-Closed Loop
EGR-Exhaust Gas Recirculation
EM-Engine Modification
OC-Oxidation Catalyst System
TR-Thermal Reactor
TWC-Three Way Catalyst System

CCV-Combustion
Chamber Valve
CFI-Central Fuel
Injection
DID-Diesel
InjectionDirect
DIP-Diesel
Injection-

Special Features

MFI-Mechanical Fuel Injection TC-Turbocharged

Prechamber

Model

Celica Sport Coupe Celica Liftback Corona 4-door Sedan Corona 5-door Liftback Corona 5-door Wagon

Engine Code

1*, 2, 3*, 4

*Engines:codes with idle-up system for air conditioned cars.

DRIVE SYSTEM:

| | | | • | | | | | |
|---------------|-------|--|-----------|--------------------------|----------------------------|----------------------------|--------------------------|-------------------------------|
| in the second | . • | Joes V | ID DESAI | IDCES ROM | - ARD SUPPLEMENTA | | age 2 | |
| X | Passe | enger Cars Li | | | | | X Gas | Diesel |
| | Manut | facturer Toyota M | lotor Con | pany | | E.O. | #A -14-44 | |
| | Engir | ne Family CTY2.4V2 | ECC0 | | CID (liter |) - Type 14 | 4.4 (2.4) I- | 4 |
| | ECS (| (Special Features) | AIP, E | GR, TWC- | CL | | | |
| Engi Cod | | Vehicle Models (If Coded see attachment) | Trans. | Equiv. Test Weight | Ign. System EI, CA, VA | Fuel System 2V | EGR Valve | Label Ident. |
| | | 4004011114110) | | | Part No. | Part No. | Part No. | Part No. |
|]** | 2 | Celica: Coupe* | M5 | 2875 | Nippondenso 19100-35030 | Aisan Kogyo 21100-35070 | 25 6 20- 35010 | pg.3 |
| 4 | | Celica: Coupe* | Α4 | | | -35151 | | |
| 3** | | Liftback | | 3000 | | | | |
|]** | | Celica: Liftback* | M5 | | | -35070 | | |
| | 2 | | | 2875 | | | | |
| 2 | | Corona: 4-Dr* Liftback* Wagon* | | 3000 | , | | | pg.4 (Corona- Wagon onl |
| 3** | | | A4 | | | -35151 | | |
| 4 | | | | | | | | |

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.

Date of Issue - sions:

| | | | | | • | - | P | age | | | |
|-----------------|---------------|-----------|----------------------------------|-----------|-----------------------------------|---------------------------------------|----------------------------|-----------------|-----------------------|---|--|
| | | | 1982 A | IR RESOL | JRCES BOA | ARD SUPPLEMENT | AL DATA SHEET | | | | |
| 4 | X Pass | enger Ca | rs Li | ght-Duty | Trucks | Medium-D | uty Vehicles | X Gas | Diesel | | |
| 100 | Manu | facturer | Toyota M | 1otor Con | npany | · · · · · · · · · · · · · · · · · · · | E.O. | #A -14-44 | | | |
| | Engi | ne Family | y CTY2.4V2 | 2ECCO | | CID (liter |) - Type14 | 14.4 (2.4) I- | 4 | | |
| | | | Features) | | | | | | | | |
| | ngine Code | (If Co | le Models oded see chment) | Trans. | Equiv. Test Wei g ht | Ign. System EI, CA, VA | Fuel System 2V | EGR Valve | Label Ident. | | |
| | | | | | | Part No. | Part No. | Part No. | Part No. | | |
| 1R | 2R | Celica: | Coupe* | M5 | 2875 | Nippondenso 19100-35030 | Aisan Kogyo 21100-35071 | 25620- 35010 | pg.3 | | |
| ,4 | R | Celica: | Coupe* | A4 | | | -35151 | | | | |
| ,3 | R | | Liftback | Liftback | Liftback | | 3000 | | | Ì | |
| 1R | · · · • | Celica: | Liftback* | M5 | | | -35071 | | | | |
| | 2R | | | | 2875 | | | | | | |
| | ,1R | Corona: | 4-Dr* Liftback* | | 3000 | | | | Pg•4 | | |
| _ | ,2R | | Wagon* | : | | | - | | (Corona- Wagon onl | | |
| | ,3R | | | A4 | | | -35151 | | | | |
| 1. ² | ,4R | | | | | · | | | | | |
| | | | | | | | | | | | |
| | | | | | | · | | | 1 | | |
| | | | | | | | | | İ | | |

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Date of Issue - 010682, R/C 82-R-15 R ions:

^{*}Add 10% to dyno test HP for air conditioning usage.

Engine family : CTY2.4V2ECCO

VEHICLE EMISSION CONTROL INFORMATION

ENGINE FAMILY : CTY2.4V2ECCO

144.4 CID

EVAP. FAMILY : EV-Rl

EXHAUST EMISSION CONTROL SYSTEM AI/EGR/02S/TWC

MAKE ALL ADJUSTMENTS WITH ENGINE AT NORMAL OPERATING TEMPERATURE, CHOKE FULL OPEN, AIR CLEANER INSTALLED, AIR CONDITIONER OFF AND TRANSMISSION IN NEUTRAL.

ENGINE TUNE-UP SPECIFICATIONS FOR ALL ALTITUDES

| IDLE SPEED (RPM) | MANUAL 700 AUTO. 750 |
|----------------------------|---|
| IGNITION TIMING (°BTDC) | 8° @ 950 RPM MAX. WITH ALL VACUUM HOSES DISCONNECTED FROM DISTRIBU- TOR AND SEALED. |
| IDLE MIXTURE SETTING | IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE-UP IS NOT RECOMMENDED. |
| FAST IDLE SPEED (RPM) | 2,600 WITH ALL VACUUM HOSES DISCON- NECTED FROM EGR VALVE AND DISTRIBU- TOR AND SEALED. |
| VALVE CLEARANCE (IN.) | INTAKE 0.008 (0.20 mm) EXHAUST 0.012 (0.30 mm) |

TOYOTA MOTOR CO., LTD.

CATALYST

THIS VEHICLE CONFORMS TO U.S. EPA AND STATE OF CALIFORNIA REGULATIONS APPLICABLE TO 1982 MODEL YEAR NEW MOTOR VEHICLES PROVIDED THAT THIS VEHICLE IS INTRODUCED INTO COMMERCE FOR SALE IN THE STATE OF CALIFORNIA ONLY.

22R

CAL

RA, RT

VEHICLE EMISSION CONTROL INFORMATION

ENGINE FAMILY : CTY2.4V2ECCO

144.4 CID

EVAP. FAMILY : EV-R2

EXHAUST EMISSION CONTROL SYSTEM AI/EGR/O2S/TWC

MAKE ALL ADJUSTMENTS WITH ENGINE AT NORMAL OPERATING TEMPERATURE, CHOKE FULL OPEN, AIR CLEANER INSTALLED, AIR CONDITIONER OFF AND TRANSMISSION IN NEUTRAL.

ENGINE TUNE-UP SPECIFICATIONS FOR ALL ALTITUDES

| IDLE SPEED (RPM) | MANUAL 700 AUTO. 750 |
|----------------------------|---|
| IGNITION TIMING (°BTDC) | 8° @ 950 RPM MAX. WITH ALL VACUUM HOSES DISCONNECTED FROM DISTRIBU- TOR AND SEALED. |
| IDLE MIXTURE SETTING | IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE-UP IS NOT RECOMMENDED. |
| FAST IDLE SPEED (RPM) | 2,600 WITH ALL VACUUM HOSES DISCON- NECTED FROM EGR VALVE AND DISTRIBU- TOR AND SEALED. |
| VALVE CLEARANCE (IN.) | INTAKE 0.008 (0.20 mm) EXHAUST 0.012 (0.30 mm) |

(54) TOYOTA MOTOR CO., LTD.

CATALYST

THIS VEHICLE CONFORMS TO U.S. EPA AND STATE OF CALIFORNIA REGULATIONS APPLICABLE TO 1982 MODEL YEAR NEW MOTOR VEHICLES PROVIDED THAT THIS VEHICLE IS INTRODUCED INTO COMMERCE FOR SALE IN THE STATE OF CALIFORNIA ONLY.

22R

CAL

RT

WGN