(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-15-62-1 Relating to Certification of New Motor Vehicles

NISSAN MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1983 model-year Nissan Motor Co., Ltd. exhaust emission control systems are certified as described below for gasoline-powered passenger cars.

Engine Family	Displacement Cubic Inches (Liters)	Exhaust Emission Control Systems (Special Features)
DNS2.8V5FAAO	146, 168 (2.4, 2.8)	Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop (Electronic Fuel Injection)

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the emission standards for this engine family to be listed on the window decal required by California Assembly-Line Test Procedures for 1983 model-year vehicles:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per Mile
0.39	7.0	0.7

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
<u>Grams per Mile</u>	Grams per Mile	Grams per Mile
0.34	2.4	0.4

NISSAN MOTOR CO., LTD.

EXECUTIVE ORDER A-15-62-1 (Page 2 of 2)

BE IT FURTHER RESOLVED: That the listed vehicle models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.15 of Title 13, California Administrative Code which includes repair or replacement of emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

This Executive Order supersedes Executive Order A-15-62, dated August 17, 1982.

Executed at El Monte, California this $\frac{13}{12}$ day of August, 1985.

K. D. Drachand, Chief Mobile Source Division

	NI	SSAN	Eng. Family:	DNS2.8V5FAAO
1983	AIR RESOURCES BOAR	D SUPPLEMENTAL D	ATA SHEET	ARB
Manufacturer <u>NI</u>	SSAN MOTOR CO., LTD	Executive (Order No. <u>A</u> -	-15-62-1
Engine Family _DM	IS2.8V5FAAO Engine	(CID) <u>168.0</u>		
Evaporative Emiss	ion FamilyEVP-EF	I-1A		
ABBREVIATIONS Distributor	Exhaust Emiss	ions Control Syst	ten	

a i se i se i se i

and the second second states and the second states and the second s

Constant of the Constant State State

Distributor	Exhaust Emissions Control System	
C-Centrifugal Advance	AI-Air Injection	OC-Oxidation Catalyst
V-Vacuum Advance	CAI-Catalyst Air Injection	PAI-Pulse Air Injection
VR-Vacuum Retard	CAB-Chamber Air Bleed	RC-Reduction Catalyst
HEI-High Energy Ignition	DD-Dual Displacement	TC-Turbo Charged
EI-Electronic Ignition	EFI-Electronic Fuel Injection	TR-Thermal Reactor
Fuel System	EGR-Exhaust Gas Recirculation	TWC-Three Way Catalyst
EFI, FI	EM-Engine Modification	(Feedback Control)
nV-nVenturi Carburetor	EFE-Early Fuel Evaporation	EGR Syst. Service
VV-Variable Venturi	ESAC-Electronic Spark Advance Control	I-Inspect, repair/replace as needed
	FI-Fuel Injection	R-Replace

Engine Code		Model	Transmission
L28FM, AL28F HL28FM, AHL28F	$H\Delta TSHAUZSHZ$	2 SEATER DELUXE	5-Speed Manual
AL28FM, AHL28F	DATSUN 280ZX DATSUN 280ZX DATSUN 280ZX DATSUN 280ZX	2 SEATER GL 2 SEATER GL (T-BAR ROOF) 2+2 SEATER GL 2+2 SEATER GL (T-BAR ROOF	5-Speed Manual
AL28FA, AHL28F.	DATSUN 280ZX DATUSN 280ZX DATSUN 280ZX DATSUN 280ZX	2 SEATER GL 2 SEATER GL (T-BAR ROOF) 2+2 SEATER GL 2+2 SEATER GL (T-BAR ROOF	Automatic)

DRIVE SYSTEM: Rear Wheel

prist hereinster.

Issue Date: 06/21/82		17.02- DNS2.8V51	FAA0-2	PAGE IS SATISFACTORY
 Revision				DATE
Date				EPA REP

		 .	NISS	SAN	Eng. Fan	uly: DNS2.8	V5FAA0
	1983 AIR	RESOURCES	BOARD	SUPPLEMENTAL	. DATA SHEE	T	ARE
Manufacturer	NISSAN	MOTOR CO.	, LTD.	Executiv	ve Order No	.A-15-62	
Engine Family	DNS2.8V	5FAAO E	Ingine (CID) 146.0			
Evaporative E	mission 1	Family E	VP-EFI-	lA			

the state of the state of the

ABBREVIATIONS

Real Property and the

ł

Distributor C-Centrifugal Advance V-Vacuum Advance VR-Vacuum Retard HEI-High Energy Ignition DD-Dual Displacement EI-Electronic Ignition Fuel System EFI, FI nV-nVenturi Carburetor VV-Variable Venturi

*** +1960<u>1</u>]

Exhaust Emissions Control System AI-Air Injection CAI-Catalyst Air Injection CAB-Chamber Air Bleed EFI-Electronic Fuel Injection EGR-Exhaust Gas Recirculation EM-Engine Modification

EFE-Early Fuel Evaporation ESAC-Electronic Spark Advance Control FI-Fuel Injection

OC-Oxidation Catalyst PAI-Pulse Air Injection RC-Reduction Catalyst TC-Turbo Charged TR-Thermal Reactor TWC-Three Way Catalyst (Feedback Control) EGR Syst. Service I-Inspect, repair/replace as needed R-Replace

and the second second and the second second

Engine Code	Model	Transmission
AL24FM, AHL24FM	DATSUN 810 MAXIMA 4 DOOR SEDAN	5-Speed Manual
L24FM, AL24FM HL24FM,AHL24FM	DATSUN 810 WAGON DELUXE DATSUN 810 MAXIMA WAGON	5-Speed Manual
AL24FA,AHL24FA	DATSUN 810 MAXIMA 4. DOOR SEDAN	Automatic
L24FA, AL24FA HL24FA,AHL24FA	DATSUN 810 WAGON DELUXE DATSUN 810 MAXIMA WAGON	Automatic

DRIVE SYSTEM: Rear Wheel

Issue Date: 06/21/82	17.02-DNS2.8V5FAA0-1	PAGE IS SATISFACTORY
Revision		
Date		EPA REP

	SATISFACTORY		S2.8V5FAA0-3	NG-20-71	1/82	Issue Date: 06/2
Comments:	AL28FA AHL28FA	L28FM AL28FM HL28FM AHL28FM	L24FA AL24FA HL24FA AHL24FA AHL24FA	L24FM AL24FM HL24FM AHL24FM AHL24FM	Eng. Code	Manufacturer Emission Con
See page 1	280ZX	DATSUN		DATSIN 810	Vehicle Models (refer to page 1)	trol
for abbreviations		M-5	L-4	M- 5	Trans	1983 X I MOTOR CO.
and	D6K82-01	HITACHI	D6K82-02	нттасні	Distributor Type: Mfgr. Part Number	AIR RESOURCES E assenger Cars LTD. Engine
evaporative emission fa	A31-622 (JECS) Injector A46-0011 (JECS) A46-0012(DKC)	Control Unit All-654806 (M/T) All-652805 (A/T) (JECS) Air Flow Meter	A31-623 (JECS) Injector A46-0011 (JECS) A46-0012 (DKC)	Control Unit All-653755 (M/T) All-655756 (A/T) (JECS) Air Flow	Fuel System Type: Mfgr. Part Number) SUPPLEMENTAL Light-Dut Ly <u>DNS2.8V5F</u> (A/C) Yes <u>X</u>
family identi	EVK72-49	EVK72-45	EVK72-49	EVK72-45	EGR System Part No. Service	ET
identification. BBV	(1) 8° BTDC @700 RPM (2) None (3) 700 RPM "D" Automatic-Drive(D)	(1) 8° BTDC @700 RPM (2) None (3) 700 RPM "N" Manual-Neutral(N)	<pre>(1) 8° BTDC @650 RPM (2) None (3) 650 RPM "D" Automatic-Drive(D)</pre>	<pre>(1) 8° BTDC @700 RPM (2) None (3) 700 RPM "N" Manual-Neutral(N)</pre>	Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed	E.O.# A-15-62-1 (CID) <u>146.0, 168.0</u>
C	DNS2.8V5FAA	Eng. Family:	NASSIV	I .		

35JUL.16 82 18:18 NISSAN TURUMI

Aster Sugar

F.035

NISSAN

E.O.# A-15-62-1 Eng. Family: DNS2.8V5FAAO

100

House and the second

ARB

17.03.00.00 Test Weight/Horsepower List - cont.

Vehicle Model	Test Weight	Time Cine	With A/C	Without A/C factor		actor
venicie model	(1bs)	1116 5126	Test HP	Coastdown Time (sec.)		Costdown Time (sec.)
DATSUN 280ZX 2 SEATER DELUXE	3125	195/70HR14	8.1	15.30		14.57
DATSUN 280ZX 2 SEATER GL	3123					14.37
DATSUN 280ZX 2 SEATER GL (T-BAR ROOF)	3250	P205/70R14			8.9	15.16
DATSUN 280ZX 2+2 SEATER GL	3230					
DATSUN 280ZX 2+2 SEATER	3 375					15.80
GL (T-BAR ROOF)	3250					15.16

Note: Since A/C installtion ratio is over 33% of this family, only "with A/C factor" is used at certification tests.

•

sue Date: 6/25/82		17.03-DNS2.8V5FAA0-2			PAGE IS SATISFACTORY		
Acvision					DATE _/_/_		
Date					EPA REP		

100.16 182 18:17 NISSAN TURUMI

.

Martin Carl Edited St.

P.034

NISSAN

E.O.# A-15-62 -1

Eng. Family: DNS2.8V5FAAO

ARB

17.03.00.00 Test Weight/Horsepower List

Vehicle Hodel	Test Weight	Tire Size	Without A/C factor		With A/C factor	
	(lbs)		Test HP	Coastdown Time(sec.)	Test HP	Coastdown Time(sec.)
DATSUN 810 MAXIMA	3125					14.74
4 DOOR SEDAN						15.40
DATSUN 810 WAGON DELUXE	3250	185/70SR14	8.3	16.82	9 . 1	15.94
DATSUN 810 MAXIMA WAGON	3375			17.46		16.52

Note: Since A/C installation ratio is over 33% of this family, only "with A/C factor" is used at certification tests.

ssue Date: 6/25/82		17.03-DNS2.	BV5FAA0-1	PAGE IS L SATISFACTORY	
Revision				DATE _/	
Date		•		EPA REP	