State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-48-13 Relating to Certification of New Motor Vehicles

ROLLS-ROYCE MOTORS LIMITED

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1984 model-year Rolls-Royce Motors Limited exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

| Engine Family | Displacement Cubic Inches (Liters) | | Exhaust Emission Control Systems (Special Features) | | |
|---------------|---------------------------------------|-------|---|--|--|
| ERR412V6FAAO | 412 | (6.8) | Air Injection - Pump Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop (Mechanical Fuel Injection) | | |

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the certification emission standards for this engine family to be listed on the window decal required by "California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles":

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides | |
|----------------|-----------------|-----------------|--|
| Grams per Mile | Grams per Mile | Grams per Mile | |
| 0.41 | 7.0 | 0.7 | |

The following are the certification emission values for the above engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides | |
|----------------|-----------------|-----------------|--|
| Grams per Mile | Grams per Mile | Grams per Mile | |
| 0.32 | 2.5 | 0.7 | |

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.15 of Title 13, California Administrative Code which includes repair or replacement of emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

M 1 W

day of June. 1983.

%. D. Drachand, Chief Mobile Source Control Division

1984 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Page 1

| Manufacturer . | Rolls-Royce Motors Limited | Executive Order No | A-48-13 |
|----------------|----------------------------|---------------------|-----------|
| Engine Family | ERR41 2V 6FAAO | Evaporative Family | No.1 |
| | • | Engine CID (Liters) | 412 (6.8) |

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance EEC-Electronic Engine Control EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard

Fuel System
CFI, CL, DID, DIP, EFI, MFI

nV-nVenturi Carburetor
"Y-Variable Venturi

Exhaust Emissions Control System

AIP-Air Injection-Pump AIV-Air Injection-Valve CL-Closed Loop EGR-Exhaust Gas Recirculation EM-Engine Modification OC-Oxidation Catalyst System TR-Thermal Reactor TWC-Three-Way Catalyst System

Special Features

CCY-Combustion Chamber Valve CFI-Central Fuel Injection DID-Diesel Injection-Direct DIP-Diesel Injection-Prechamber EFI-Electronic Fue 1 Injection MFI-Mechanical Fue 1 Injection TC-Turbocharged

VEHICLE MODELS:

Rolls-Royce Silver Spirit
Rolls-Royce Silver Spur
Rolls-Royce Corniche Convertible
Rolls-Royce Camargue
Bentley Mulsanne
Bentley Mulsanne L
Bentley Corniche Convertible

DRIVE SYSTEM: Front Engine/ Rear -Wheel Drive

E.O. #A-48-13
1984 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

| | facturer Rolls-Rone Family ERR412 | Page 2 Engine Code A | | | | | |
|--|---|----------------------|------------------------------|------------------------------------|--|-----------------|-----------------|
| ECS (Special Features) AIP, EGR, TWC, CL (MFI) | | | | CID (Liter)- Type _ | 412 (6.8) - V8 | | |
| Engine Code | Vehicle Models (If Coded see attachment) | Trans. | Equiv. Test Weight | Ign. System | Fuel System | EGR Valve | Label Ident. |
| | | | | CA, VA | Part No. | Part No. | Part No. |
| A | Rolls-Royce Silver Spirit Silver Spur Corniche Conv. Camargue | A 3 | 5250 5250 5500 5500 | Lucas: 41941 RR: UE 44406 | Metering Unit: Bosch: O 438 080 016 | GM: 7045068 | UE 44964 |
| | Bentley Mulsanne Mulsanne L Corniche Conv. | | 5250 5250 5500 | UE 47400 | RR: UE 43382 | RR: UE 40755 | |
| | | į . | | | | | |
| | | | | | | | |
| | | | | | | · | |
| | | | | · | | | |
| | | | | | | | |
| | | | | | .* | | |
| | | | | | · | | |

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.

Date of Issue -

E.O. A-48-13

MANUFACTURER'S HP LIST

| Vehicle Models | Equiv Test Weight | RLHP (incl 10%) for ACU | |
|-----------------------|-------------------------|-------------------------------|--|
| Rolls-Royce | | | |
| Silver Spirit | 5250 | 13.9 | |
| Silver Spur | 5250 | 13.9 | |
| Silver Spur Limousine | 5500 | 13.9 | |
| Corniche Conv. | 5500 | 14.8 | |
| Camargue | 5500 | 14.7 | |
| Bentley | | | |
| Mulsanne | 5250 | 13.9 | |
| Mulsanne L | 5250 | 13.9 | |
| Corniche Conv. | 5500 | 14.8 | |

| Issue Date | 6 Apr '83 | © Rolls-Royce Motors Limited 1984 | | | |
|---------------|------------|-----------------------------------|--|--|--|
| Revision Date | 31 Oct '84 | | | | |