

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-74 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1985 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family	Displacement Cubic Inches (Liters)		Exhaust Emission Control Systems (Special Features)		
FTY2.8V5FBB6	168.4	(2.8)	Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop (Electronic Fuel Injection)		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the certification emission standards for this engine family to be listed on the window decal required by "California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles":

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	
Grams per Mile	Grams per Mile	<u>Grams per Mile</u>	
0.39	7.0	0.7	

The following are the certification emission values for the above engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	
Grams per Mile	Grams per Mile	Grams per Mile	
0.22	2.7	0.3	

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.15 of Title 13, California Administrative Code which includes repair or replacement of emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3154 day of August, 1984.

K. D. Drachand, Chief Mobile Source Division

Bob Gross for

17.10.00 Supplemental data sheets

1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

		Pagel	
Manufacturer Toyota Motor Corporat	ion Executive Order No. $A-14-$	14	
Engine Family FTY2.8V5FBB6	Evaporative Family EV	/-ME	
•	Engine CID (Liters) 168	.4 (2.8)	
ABBREVIATIONS			
Ignition System	Exhaust Emissions Control System	Special Features	
CA-Centrifugal Advance	AIP-Air Injection-Pump	CCV-Combustion	
EEC-Electronic Engine Control	AIV-Air Injection-Valve	Chamber Valve	
EI-Electronic Ignition	CL-Closed Loop	CFI-Central Fuel	
FSAC-Electronic Spark Advance	EGR-Exhaust Gas Recirculation	Injection	
Control	EM-Engine Modification	DID-Diesel	
VA-Vacuum Advance	OC-Oxidation Catalyst System	Injection-	
VR-Vacuum Retard	TOC-Trap Oxidizer Continual	Direct	
	TOP-Trap Oxidizer Periodical	DIP-Diesel	
	TR-Thermal Reactor	Injection-	
	TWC-Three Way Catalyst System	Prechamber	
Fuel System		EFI-Electronic	
CFI, CL, DID, DIP, EFI, MFI		Fuel Injection	
nV-nVenturi Carburetor		IC-Intercooler	
W-Variable Venturi		MFI-Mechanical	
		Fuel Injection	
	- C. OY1-	TC-Turbocharged	
VEHICLE MODELS :	Celiea Supra		
MA61L-BIMQ -BLPQ	FA) MX72LG-XWPGFA-Cressida Wg FA) MX73L-XEMGFA} Cressida Sdn	•	

DRIVE SYSTEM : Front Engine/Rear - Wheel Drive

Page : 17-62

Issued: 06/06/84

		111	7//	
E.O.	#A	-14-	19	

1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

x Passen	ger Cars Li	ght-Dut	y Trucks	Medium-	Duty Vehicles	s <u>x</u> Gas	Diesel
Manufactur	er Toyo	ta Moto	r Corpora	tion	Page	2	
Engine Fam	nily FTY2	.8V5FBB	6	CI	Engine Code D (Liter) - 1		4
ECS (Speci	al Features)	CL + :	EGR + TWC	(EFI)	Type	6 cyl. in-li	ne
Engine code	Vehicle Models (If Coded see attachment) Refer to 08.13.03.00]	Equiv. Test Weight	EEC, EI, ESAC Part No. [Computer] [Knock sensor]	Part No. [Computer] [Air flow		Label Iden
1	MA611-BIMQFA	M5	3,375	1	89661-22080 22250-43150 23250-45011		11298-43190
2	MA61L-BLPQFA	A4	3,500	1	89661-22090 22250-43150 23250-45011		
3	MX73L-XEMGFA	м5	3,500		89661-22080 22250-43230 23250-45011	, i	
4	MX73L-XEPGFA MX72LG-XWPGFA	A4	3,500 3,500 *1 3,375	89661-22090 89615-22010	89661-22090 22250-43230 23250-45011		

Note *1: After running change 85-R-7

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.

Page : 17-63

Issued: 06/06/84 85-R-7: 11/19/84