(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-91 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1986 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

| Engine Family | Displacement Cubic Inches (Liters) | Exhaust Emission Control Systems (Special Features) | | |
|---------------|---------------------------------------|--|--|--|
| GTY2.0V5FBH9 | 121.9 (2.0) | Exhaust Gas Recirculation Three-Way Catalyst with Closed Loc (Electronic Fuel Injection) | | |

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides |
|----------------|-----------------|-----------------|
| Grams per Mile | Grams per Mile | Grams per mile |
| 0.39 | 7.0 | 0.7 |

The following are the certification emission values for this engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides | |
|-----------------------|-----------------|-----------------|--|
| <u>Grams per Mile</u> | Grams per Mile | Grams per Mile | |
| 0.20 | 2.3 | 0.3 | |

TOYOTA MOTOR CORPORATION

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

18 CH day of February, 1986.

Maun

K. D. Drachand, Chief Mobile Source Division

Supplemental data sheets 17.10.00

1986 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Fuel Injection

Fuel Injection

IC-Intercooler

MFI-Mechanical

TC-Turbocharged

| | | Page | 1 |
|---------------------------------------|----------------------|-------------|---|
| Manufacturer Toyota Motor Corporation | Executive Order No. | A-14-91 | _ |
| Engine Family <u>GIY2.0V5FBH9</u> | Evaporative Family _ | EV-E | _ |
| | Engine CID (Liters) | 121.9 (2.0) | |

ABBREVIATIONS

¢

| Ignition System | Exhaust Emissions Control System | Special Features |
|-------------------------------|----------------------------------|------------------|
| CA-Centrifugal Advance | AIP-Air Injection-Pump | CCV-Combustion |
| EEC-Electronic Engine Control | AIV-Air Injection-Valve | Chamber Valve |
| EI-Electronic Ignition | CL-Closed Loop | CFI-Central Fuel |
| ESAC-Electronic Spark Advance | EGR-Exhaust Gas Recirculation | Injection |
| Control | EM-Engine Modification | DID-Diesel |
| VA-Vacuum Advance | OC-Oxidation Catalyst System | Injection- |
| VR-Vacuum Retard | TOC-Trap Oxidizer Continual | Direct |
| | TOP-Trap Oxidizer Periodical | DIP-Diesel |
| | TR-Thermal Reactor | Injection- |
| | TWC-Three Way Catalyst System | Prechamber |
| Fuel System | | EFI-Electronic |

CFI, CL, DID, DIP, EFI, MFI nV-nVenturi Carburetor VV-Variable Venturi

VEHICLE MODELS :

Celica ST162L-BOMVFA -BIMVFA -BCPVFA

DRIVE SYSTEM : Front Engine/Front - Wheel Drive

: 17-72.1 Page Issued : 01/10/86

E.O. #A-14-91

1986 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

| <u>x</u> Passenger Cars | Light-Duty Trucks | Medium-Duty Vehicl | es <u>x</u> Gas Diesel |
|-------------------------|--------------------------|----------------------|------------------------------|
| Manufacturer | Toyota Motor Corporation | Page | 2 |
| Engine Family | GIY2.0V5FBH9 | Engine Code | 1 thru 4 |
| ECS (Special Feature | s) <u> </u> | CID (Liter)- Type | 121.9(2.0) 4 cyl. in-line |

| Engine | Vehicle Models (If Coded see | Trans. | Equiv. Test | Ign. System EEC,EI,ESAE | | EGR Valve | Label Ident. |
|--------|--|--------|----------------|----------------------------|---|-----------|--------------|
| code | attachment) Refer to 08.13.03.00 | | Weight | Part No. [Computer] | Part No. [Computer] [Air flow meter] [Injector] | Part No. | Part No. |
| 1, 2 | ST162L-BCMVFA -BLMVFA | м5 | 3,125 | 89661-20160 | 89661-20160 22250-74060 23250-74010 | | 11298-74151 |
| 3, 4 | ST162L-BCPVFA | A4 | 3,125 | | | | |

Comments : See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.

¢.

Page : 17-72.2 Issued : 01/10/86 Rev. 1 : 01/10/86