

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-35
Relating to Certification of New Motor Vehicles

SAAB-SCANIA AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1987 model-year Saab-Scania AB exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

<u>Engine Family</u>	<u>Displacement Cubic Inches (Liters)</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
HSA2.0V5FTBX	121.1 (2.0)	Three-Way Catalyst Heated Oxygen Sensor (Electronic Fuel Injection) (Turbocharger) (Intercooler)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per mile</u>
0.41	7.0	0.7

The following are the certification emission values for this engine family:

<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0.18	1.4	0.2

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 23rd day of September, 1986.


K. D. Drachand, Chief
Mobile Source Division

1987 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O. # A-22-35

Page 1

Manufacturer Saab-Scania AB Engine Family HSA2.0V5FTBX
 Evaporative Family H-900-4 Engine Type Otto 16-Valve 4-Cyl. In-line
 Liters (CID) 2.0 (121.1)

ABBREVIATIONS

<u>Ignition System</u>	<u>Exhaust Emissions Control System</u>	<u>Special Features</u>
CA-Centrifugal Advance	AIP-Air Injection-Pump	CCV-Combustion Chamber Valve
EEC-Electronic Engine Control	AIV-Air Injection-Valve	CFI-Central Fuel Injection
EI-Electronic Ignition	CL-Closed Loop	DID-Diesel Injection-Direct
ESAC-Electronic Spark Advance Control	EGR-Exhaust Gas Recirculation	DIP-Diesel Injection-Prechamber
VA-Vacuum Advance	EM-Engine Modification	EFI-Electronic Fuel Injection
VR-Vacuum Retard	OC-Oxidation Catalyst System	IC-Intercooler or aftercooler
	SPL-Smoke Puff Limiter or Throttle Delay	MFI-Mechanical Fuel Injection
	TOC-Trap Oxidizer, Continual	TC-Turbocharger
	TOP-Trap Oxidizer, Periodical	
	TR-Thermal Reactor	
	TWC-Three-Way Catalyst System	

Fuel System

CFI, CL, DID, DIP, EFI, MFI
 nV-nVenturi Carburetor

VEHICLE MODELS:

<u>Engine Code</u>	<u>Car Line</u>	<u>Transmission</u>
202TM5AC	900T-3CKL Hatchback 900T-3CKLEAG Hatchback 900T-3CKLSPG Hatchback 900T-2-Door Convertible	M5
202TA3AC	900T-3CKL Hatchback 900T-3CKLEAG Hatchback 900T-2-Door Convertible	A3

Engine: Front X Mid. _____ Rear _____
 Drive: FWD X RWD _____ 4WD Full Time _____ 4WD Part Time _____

1987 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars xx Light-Duty Trucks _____ Medium-Duty Vehicles _____ Gas xx Diesel _____Manufacturer Saab-Scania AB Engine Family HSA2.0V5FTBX (900T)Liter (CID) 2.0 (121.1) Eng. Type S.I. 16-Valve 4-Cyl. In-LineEmission Control Sys. (Special Features) TWC, CL (EFI, TC, IC)

Engine Code	Vehicle Models (If Coded see Attachment) (HP)	Trans. Type	Equiv. Test Weight	Ign. System (ECU) Part No.	Fuel System Part No.	EGR Valve Part No.	Catalyst Part No.
202TM5AC	900T-3CKL	M5	3125	Distributor	Electronic Control Unit Saab Pt. No. -75 61 806 Bosch Pt. No. -75 36 709 Bosch Pt. No. -0280000538	Not Applicable	75 33 540
	900T-EAG-3CKL	M5	3250	Saab Pt. No.			
	900T-SPG-3CKL	M5	3250	-75 61 806			
	900T Convertible	M5	3250	Bosch Pt. No. -0237507007			
202TA3AC	900T-3CKL	A3	3250	Hall Effect Power Stage	Air Mass Meter Saab Pt. No. -93 90 220 Bosch Pt. No. -0227100139 Bosch Pt. No. -0280212005		
	900T-EAG-3CKL	A3	3250	Saab Pt. No.			
	900T Convertible	A3	3375	-93 90 220			
				Bosch Pt. No. -0227100139			
				Ignition Coil			
				Saab Pt. No.			
				-85 73 834			
				Bosch Pt. No. -0221122327			

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Add 10% to dyno test Hp for air conditioning usage.