8.0. Book

(Page 1 of 2)

## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-265-4 Relating to Certification of New Motor Vehicles

## BITTER AUTOMOBILE

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1987 model-year Bitter Automobile exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family	Displacer Cubic Inches		Exhaust Emission Control Systems (Special Features)
HBT3.0V5FA19	181	(3.0)	Three-Way Catalyst Heated Oxygen Sensor (Electronic Fuel Injection)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per mile
0.41	7.0	0.7

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per Mile
0.24	1 4	0.6

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this  $\mathcal{U}^{a}$  day of August, 1987.

Mirumo

K. D. Drachand, Chief Mobile Source Division

				Page 1
Macacturer <u>Bitter Automobile</u>		Engine Family	HBT 3.0V5 F	-A19
Evaporative Family BT-A		Engine Type	L-6	
		Liters (CID) _	3.0 (181)	
ABBREVIATIONS				
Ignition System	Exhaust Er	nissions Control S	System	Special Features
CA-Centrifugal Advance ECU-Electronic Control Unit EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard	AIV-Air In DBC-Dual E EGR-Exhaus EIC-Electr EM-Engine OC-Oxidati OS-Oxygen HOS-Heated SPL-Smoke Throttle TOC-Trap C	d Oxygen Sensor Puff Limiter or e Delay Oxidizer, Continua Oxidizer, Periodic	ontrol	CCV-Combustion Chamber Valve CFI-Central Fuel Injection or Throttle Body Injection DID-Diesel Injection- Direct DIP-Diesel Injection- Prechamber EFI-Electronic
Fire System  CFI, CL, DID, DIP, EFI, MFI nV-nVenturi Carburetor	WUOC-Warm-	-Way Catalyst -Up Oxidation Cata n-Up Three-Way Cat		Fuel Injection IC-Intercooler or Aftercoole MFI-Mechanical Fuel Injection OBD-On-Board Diagnostics TC-Turbocharger
VEHICLE MODELS: Bitter SC 3.	0			

Engine:	Front X	Mid	Rear	
Drive:	FWD	RWD X	4WD Full Time	4WD Part Time

é.	10 a =	ATD DE	COURCES BO	ADD CUDDLEMENT	AL DATA CUCET	E.O. # A-	265-4
Daccongon	Cars $X$ Light.	•		ARD SUPPLEMENT		Page Can V De	2
		, .					iesei
	rer <u>Bitter Aut</u>					PINICA	
	3.0(181)						
·Emission (	Control Sys. (Spec	cial Feat	ures) <u>T</u> i	WC , HOS, LEPF.	I)		
Engine Code	Vehicle Models (If Coded see attachment)	Trans. Type	Equiv. Test Weight	Ign. System (ECU)	Fuel System	EGR Valve	Catalyst
	(Dyno Hp)		wergnt	Part No.	Part No.	Part No.	Part No.
3.0 <i>E</i>	Bitter SC 3.0	M5	3750	0 280 001	0 280 160	N/A	1130
	(8.8)	A3		122	205		88232 000
						,	
				•			
6							
Comments: Please ref edment.	See page one for er to manufacture If two test wei	r's HP 11	ist for co	rrect dyno tes	t HP settings	based on mod	del and
Date of Is	sue <u>8/5/87</u>		Revisio	ns:	<del></del>	* of the state of	