E.D. Bark

(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-354 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Ford Motor Company exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

| Engine Family | Displacement Liters (Cubic Inches) | Exhaust Emission Control Systems (Special Features) |
|---------------|---------------------------------------|--|
| JFM3.OV5FED7 | 3.0 (181) | Heated Oxygen Sensor |
| | | Exhaust Gas Recirculation Three-Way Catalyst |
| | | (Electronic Port Fuel Injection) (On-Board Diagnostics) |

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides |
|-----------------------|-----------------|-----------------|
| <u>Grams</u> per Mile | Grams per Mile | Grams per mile |
| 0.41 | 7.0 | 0.7 |

The following are the certification emission values for this engine family:

| Hydr ocar bons | Carbon Monoxide | Nitrogen Oxides |
|-----------------------|-----------------|-----------------|
| Grams per Mile | Grams per Mile | Grams per Mile |
| 0.15 | 2.2 | 0.4 |

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles". FORD MOTOR COMPANY

EXECUTIVE ORDER A-10-354 (Page 2 of 2)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided evidence of federal certification of vehicle models listed in the attachments which are not available as California-certified models.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 4th day of August, 1987.

K. D. Drachand, Chief Mobile Source Division

| × | | e.o.# <u>A-10-354</u> - |
|---|---|---------------------------------|
| 1988 AIR RES | OURCES BOARD SUPPLEMENTAL DATA SHEET | |
| | 5 | Page 1 |
| Manufacturer Ford Motor Company | Engine Family JFM3.0VFED7 | |
| | Engine Type <u>V6</u> | |
| Evaporative Family <u>8HM</u> | Engine Type | |
| | Liters (CID) <u>3,0 (181)</u> | |
| | | |
| ABBREVIATIONS | | |
| T | Exhaust Emissions Control System | Special Features |
| Ignition System | Exhaust Emissions donetor bystem | |
| | | |
| CA-Centrifugal Advance | AIP-Air Injection Pump | CCV-Combustion Chamber Valve |
| ECU-Electronic Control Unit | AIV-Air Injection Valve DBC-Dual Bed Catalyst | CFI-Central Fuel |
| EI-Electronic Ignition ESAC-Electronic Spark Advance | EGR-Exhaust Gas Recirculation | Injection or |
| Control | EIC-Electronic Injection Control | Throttle Body |
| VA-Vacuum Advance | EM-Engine Modification | Injection |
| VR-Vacuum Retard | OC-Oxidation Catalyst | DID-Diesel |
| | OS-Oxygen Sensor | Injection- |
| | HOS-Heated Oxygen Sensor | Direct |
| k . | SPL-Smoke Puff Limiter or | DIP-Diesel |
| | Throttle Delay | Injection- |
| | TOC-Trap Oxidizer, Continual | Prechamber EFI-Electronic |
| | TOP-Trap Oxidizer, Periodical | Fuel |
| | TWC-Three-way Catalyst WUOC-Warm-up Oxidation Catalyst | Injection |
| | WUTWC-Warm-up Three-way Catalyst | IC-Intercooler |
| | worwo-warm-up inice way odearyoe | or Aftercooler |
| | | MFI-Mechanical |
| | | Fuel |
| Fuel System | Y | Injection |
| | | OBD-On-Board |
| CFI, CL, DID, DIP, EFI, MFI | | Diagnostics |
| nV-nVenturi Carburetor | | TC-Turbocharger |
| VEHICLE MODELS: | | |
| TAURUS SEDAN 54D | | |
| TAURUS S/W 74D | | |
| SABLE SEDAN 54D | | |
| SABLE S/W 74D | | |
| | | |

/

F 'ne: Front XXX Mid ____ Rear ____ : FWD XXX RWD ___ 4WD Full Time ____ 4WD Part Time ____

fcsds30b.wp

• • •

| * * * | | | | | τ | E.O. # <u>A-1(</u> | 1-354- |
|----------------------|--|----------------|---|--|--|----------------------------------|---------------------------------|
| | 1988 | AIR RESOU | RCES BOAR | D SUPPLEMENTAL | | | |
| Passenger (| Cars <u>XXXXX</u> Light-Du | ty Trucks | Me | edium-Duty Vehi | cles Gas | xXXXXX Dies | e <u>1</u> sel |
| Manucture | er FORD MOTOR COMP | ANY | <u></u> | Engine Fami | ly JFM3.0V5FE | 2D7 | |
| Liter (CID) | 3.0 (181) | | | Eng. Typ | De <u>V6</u> | | |
| Emission Co | ontrol Sys. (Specia | l Feature | es) <u>EEC, E</u> | ESAC.CL.HOS.EGF | R.TWC.EFI | | |
| Engine Code | Vehicle Models (If Coded see attachment) (Dyno Hp) | Trans. Type | Equiv. Test Weight | Ign. System (ECU) Part No. -12A650- | Fuel System Injector Part No. -9F593- | EGR Valve Part No. -9D475- | Catalyst Part No. -5F250- |
| 8510R00A 810SR00N | TAURUS SEDAN (7.5*;6.6**) TAURUS S/W (8.4) SABLE SEDAN (7.5*;6.6**) SABLE S/W (8.4) TAURUS SEDAN (6.8*;6.0**) TAURUS S/W (7.6) SABLE SEDAN (6.8*;6.6**) SABLE S/W (7.6) | A4 - OD | 3500 3625 3500 <u>2</u> / 3625 3375 3625 3500 3625 | ESDFMB | E59E AB | E6AEBA | E7DCKA OR E7DCKB |

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing. * WITH P195 TIRES; ** WITH P205 TIRES; <u>2</u>/ FORD ELECTS TO TEST AT 3625

f of Issue:

fcsds30.wp