## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-14-119-1 Relating to Certification of New Motor Vehicles

## TOYOTA MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Toyota Motors Corporation exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

Engine Family	Displacement Liters (Cubic Inches)		Exhaust Emission Control Systems (Special Features)		
JTY2.2T5FBE2	2.2	(136.5)	Exhaust Gas Recirculation Three-Way Catalyst Heated Oxygen Sensor Oxygen Sensor (After Catalyst) (Electronic Port Fuel Injection) (On-Board Diagnostics)		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Loaded Vehicle Weight	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per mile	Nitrogen Oxides Grams per Mile
3751-5750	0.50	9.0	1.0

The following are the certification emission values for this engine family:

Loaded Vehicle Weight	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile
3751-5750	0.26	2.3	0.4

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seg.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order supersedes Executive Order A-14-119 dated August 26, 1987.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 15 day of October, 1987.

K. D. Drachand, Chief Mobile Source Division

a. F. Donnelly (for KDD)

17.11.00 Supplemental data sheets

11.11.00 Suppremental data sheers							
1988 AIR RE	SOURCES BOARD SUPPLEMENTAL DATA SH						
		Page <u> </u>					
Manufacturer Toyota Motor Cori	oration Engine Family	2T5FBE2					
Evaporative Family	Engine Type 4 cyl.	in-line					
	Liters (CID)2.2						
ABBREVIATIONS							
Ignition System	Exhaust Emissions Control System						
CA-Centrifugal Advance	AIP-Air Injection-Pump	CCV-Combustion Chamber Valve					
ECU-Electronic Control Unit	AIV-Air Injection-Valve DBC-Dual Bed Catalyst	CFI-Central Fuel					
EI-Electronic Ignition ESAC-Electronic Spark Advance		Injection					
Control	EIC-Electronic Injection Control	DID-Diesel					
VA-Vacuum Advance	EM-Engine Modification	Injection-					
VR-Vacuum Retard	OC-Oxidation Catalyst	Direct					
	OS-Oxygen sensor	DIP-Diesel Injection-					
	HOS-Heated Oxygen Sensor SPL-Smoke Puff Limiter or	Prechamber					
	Throttle Delay	EFI-Electronic					
	TOC-Trap Oxidizer, Continual	Fuel Injection					
Fuel System	TOP-Trap Oxidizer, Periodical	IC-Intercooler					
CFI, CL, DID, DIP, BFI, MFI	TWC-Three-Way Catalyst WUOC-Warm-Up Oxidation Catalyst	or aftercooler MFI-Mechanical					
nV-nVenturi Carburetor	WUTWC-Warm-Up Three-Way Catalyst	Fuel Injection					
	•••••	OBD-On-Board					
		Diagnostics					
		TC-Turbocharger					
VEHICLE MODELS :							
Van 4	MD (Passenger)						
Y	R31LG-MQEA						
	-PQEA						
Engine: Front x Mid	Rear						
	4WD Full time 4WD Pa	rt time <u>x</u>					
		<del></del>					
•							

Page : 17.11-57
Issued : 05/26/87

E.O. # A- 14-119-1

1988	AIR	RESOURCES	BOARD	SUPPLEMENTAL	DATA	SHEET
	* * * * * *	1/20001/000		DALT BRITISH TURB	DUID	

Passenger	Cars Light-Du	ity Truc	cks <u>x</u>	Medium-Duty	Vehicles	Gas x Die	esel
Manufactur	er <u>Toyota Mo</u>	tor Corp	oration	n Engine	e family	JTY2.2T	FBE2
Liter (CID	2.2	(136.5)		Eng.	Type <u>4 cyl</u>	in-line	
Emission C	Control Sys. (Spec	cial Fe	atures)	EGR	+ OS + HOS -	TWC (EFI +	OBD)
Engine code	Vehicle Models (If Coded see attachment) (Dyno Hp: Refer to 08.13.03.00)	Trans. Type	Test	EEC, EI, ESAC	Part No.	EGR Valve	Catalyst Part No.
1, 2	YR31LG-MQEA	м5	3,875 4,000	89661-28090	89661-28090 22250-73010 23250-73010		18450-73120
1R1, 2R1	YR31LG-MQEA			89661-28091	89661-28091 22250-73010 23250-73010		
3, 4	YR31LG-PQEA	A4	3,875 4,000	89661-28090	89661-28090 22250-73010 23250-73010		•
3R1, 4R1	YR31LG-PQEA			89661-28091	89661-28091 22250-73010 23250-73010		

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Page : 17.11-58

Issued: 05/26/87 88-TR-12: 03/04/88