(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-43 Relating to Certification of New Motor Vehicles

SAAB-SCANIA AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Saab-Scania AB exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family	D	isplacement	Exhaust Emission Control Systems		
	Liter:	s (Cubic Inches)	(Special Features)		
KSA2.0V5FNB8	2.0	(121.1)	Three-Way Catalyst Heated Oxygen Sensor (Electronic Port Fuel Injection) On-Board Diagnostics (Exempted)		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	
(Grams per Mile)	(Grams per Mile)	(Grams per Mile)	
0.41	7.0	0.4	

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides		
(Grams per Mile)	(Grams Der Mile)	(Grams Der Mile)		
0 24	18	0.3		

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year. SAAB-SCANIA AB

1

EXECUTIVE ORDER A-22-43 (Page 2 of 2)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 <u>et seq</u>.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _____ day of August, 1988.

K. D. Drachand, Chief Mobile Source Division

Attachment 3

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Page 1

-22-43

-17-09

Lianufacturer <u>Saab-Scania</u> AB	Engine Family _KSA2.0V5FNB8
Evaporative Family <u>K-900-5</u>	Engine Type S.I., 16-valve, 4 cyl., In-Line
	Liters (CID) 2.0L (121.1 CID)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance ECU-Electronic Control Unit EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard

Jel System

CFI, CL, DID, DIP, EFI, MFI nV-nVenturi Carburetor

Exhaust	Emissions	Control	System
Name and Address of the Owner, which the			

AIP-Air Injection-Pump AIV-Air Injection-Valve DBC-Dual Bed Catalyst EGR-Exhaust Gas Recirculation EIC-Electronic Injection Control EM-Engine Modification OC-Oxidation Catalyst OS-Oxygen Sensor HOS-Heated Oxygen Sensor SPL-Smoke Puff Limiter or Throttle Delay TOC-Trap Oxidizer, Continual TOP-Trap Oxidizer, Periodical TWC-Three-Way Catalyst WUOC-Warm-Up Oxidation Catalyst WUTWC-Warm-Up Three-Way Catalyt Special Features

E.O. #

CCV-Combustion Chamber Valve CFI-Central Fuel Injection or Throttle Body Injection DID-Diesel Injection-Direct DIP-Diesel Injection-Prechamber EFI-Electronic Fuel Injection IC-Intercooler or Aftercooler MFI-Mechanical Fuel Injection OBD-On-Board Diagnostics TC-Turbocharger

VEHICLE MODELS:

Saab	900	3-door
Saab	900	4-door
Saab	900S	3-door
Saab	900S	4-door

Ingine:	Front	έ <u>χ</u>	Mid	Rear	
Drive:	FWD	<u> </u>	RWD	4WD Full Time 4WD Part Time	

-17-11--__ E.O. # A-22

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

X Passenger Cars _____ Light Duty Trucks ____ Medium Duty Vehicles _X Gas ____ Diesel

Manufacturer Saab-Scania AB

Engine Family KSA2.0V5FNB8

ECS and (Special Features) TWC, HOS, (EFI)

CID (liter) - Engine Type 121.1 (2.0) S.I., 16-valve, 4-Cyl., In-Line

Engine Code	Vehi (If (At (HP)	cle Models Coded see tachment))	Trans.	Equiv. Test Weight	Ign. System Part No.	Fuel System Part No.	EGR Valve Part No.	Catalyst Part No.
2022I13M	900 900 900S 900S	3-door 4-door 3-door 4-door	M5 M5 M5 M5	3000 3125 3125 3125 3125	<u>Distributor</u> Saab #748443 Bosch #0 237 501 010	Electronic <u>Control Unit</u> Saab #7487135 Bosch #9280 - 000 564	N/A	7533532 7533797 (alternate
					EZK Control Unit Saab #74 84 - 504 Bosch #0 227 400 150	Air Mass Meter Saab #75 38 - 655 Bosch #0 280 212 013		
2022I13A	900 900 900S 900S	3-door 4-door 3-door 4-door	A3 A3 A3 A3	3000 3125 3125 3125 3125	Ignition Coil <u>w/Power Stage</u> Saab #7538796 Bosch #0 221 600 055	<u>Oxygen Sensor</u> Saab #9392762 Bosch #0 258 003 028		
NOTE: F	OR ADDI	TIONAL PAR	t number	S - SEE	SECTION 20N, F	AGE 10		

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Add 10% to dyno test Hp for air conditioning usage.