State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-23-66 Relating to Certification of New Motor, Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family		splacement (Cubic inches)	Exhaust Emission Control Systems (Special Features)
KHN1.5V5FBC0	1.5	(91)	Oxygen Sensor Three-Way Catalyst (Central Fuel Injection) (On-Board Diagnostics)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides		
(Grams per Mile)	(Grams per Mile)	(Grams per Mile)		
0.39	7.0	0.7		

The following are the certification emission values for this engine family:

Hydrocarbons		Carbon Monoxide	Nitrogen Oxides		
(Grams per Mi		(Grams per Mile)	(Grams per Mile)		
0.08	,	1.3	0.3		

BE IT FURTHER RESOLVED: That the listed models are certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying to the optional NOx standard by providing evidence that there are sufficient projected sales of vehicles certifying to the primary NOx

emission standard, or is, allowed a delay in implementation under small volume manufacturer provisions, or is allowed a delay in implementation under the "in ileu" standards, or is certifying passenger cars weighing more than 5250 ibs. loaded vehicle weight.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model—year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compilance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.), and with the 2 year/24,000 mile warranty provisions of Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 22 MM day of August, 1988.

K. D. Drachand, Chief Mobile Source Division

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

.O.3	#	Α	_	2	3-	6	6

Page	1	

Manufacturer	HONDA	Engine Family	KHN1.5V5FBC0
Evaporative Family	89FD	Engine Type	I - 4
		Liters (CID)	1.5 (91)
ABBREVIATIONS			
Ignition System	Exhau	st Emissions Control Syst	em Special Features
CA-Centrifugal Advance ECU-Electronic Control I EI-Electronic Ignition ESAC-Electronic Spark Ad Control VA-Vacuum Advance VR-Vacuum Retard	Jnit AIV-A EGR-E Ivance EIC-E EM-En SPL-S T TOC-T TOP-T DBC-D OC-Ox	ir Injection - Pump ir Injection - Valve xhaust Gas Recirculation lectronic Injection Contr Diesel Only) gine Modification moke Puff Limiter or hrottle Delay rap Oxidizer, Continual rap Oxidizer, Periodical ual Bed Catalyst idation Catalyst hree-way Catalyst	CFI-Central Fuel Injection or Throttle Body Injection EPFI-Electronic Port Fuel Injection MPFI-Mechanical Port Fuel Injection SFI-Sequential Fuel Injection DID-Diesel Injection- Direct DIP-Diesel Injection-
Fuel System CFI, EPFI, MPFI, SFI, DID, DIP, HOS, OS nV-nVenturi Carburetor VV-Variable Venturi Carl	WUOC- WUTWC OS-Ox HOS-H	Warm-Up Oxidation Catalys -Warm-Up Three-Way Cataly ygen Sensor eated Oxygen Sensor	rechamber Prechamber
VEHICLE MODELS:			
Civic HB STD			
•			
Engine : Front X	Mid.	Rear	
Drive : FWD X			4WD Part Time

080187

ISSUED: 05/31/88

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.D.	. #	A -	23-	- 66

Page	2	

Manufactu Liter (CI	rer HONDA D) 1.5 (9) Control Sys. (Spe	1)		Engine Family Engine Type	y KH	N1.5V5FBC0 - 4	
Engine Code	Vehicle Models (If Coded see attachment) *(Dyno HP)	Trans. Type	Equiv. Test Weight	Ign. System (ECU) Part No. (Vendor's)	Fuel System Part No. (Vendor's)	EGR Valve Part No. (Vendor's)	Catalyst Part No. (Vendor's)
KB1 KB1/1	Civic HB STD	M4	2375	EI & ESAC Toyo Denso Distributor: 30100-PM5 -A031 (TD-01U) ECU: 37820-PM5 -L160 (37820-PM5 -L16)	CFI Denshi Giken ECU: 37820-PM5 -L160 (37820-PM5 -L16)	N/A	18150-PM8 -A014 (HCB) 18150-PM8 -A024 (HCB)

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing. Add 10% to dyno test HP for air conditioning usage.

*:	Please	refer	to	page	08-1	in	1989	Applica	ation.

Date	of	Issued	05/31/88	Revisions