State of Cailfornia AIR RESOURCES BOARD

EXECUTIVE ORDER A-86-104 Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Mitsubishi Motors Corporation emission control systems are certified as described below for gasoline-powered light-duty trucks:

Engine Family	Displacement <u>Liters (Cubic Inches)</u>		Exhaust Emission Control Systems (Special Features)			
KMT2.0T5FC19	2.0	(121.9)	Exhaust Gas Recirculation Oxygen Sensor Three-Way Catalyst On-Board Diagnostics (Exempted) (Sequential Fuel Injection)			

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Loaded Vehicle Weight(Ibs.)	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	(Grams per Mile)	(Grams per Mile)	(Grams per Mile)
0 - 3750	0.39	9.0	0.4

The following are the certification emission values for this engine family:

Loaded Vehicle Weight(Ibs.)	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
	(Grams per Mile)	(Grams per Mile)	(Grams per Mile)
0 - 3750	0.18	1.5	0.2

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Maifunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compilance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _____ day of July, 1988.

K. D. Drachand, Chief Mobile Source Division

E.O. # <u>A-86-104</u>

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1/2

Manufacturer: <u>Mitsubishi Motors Corporation</u>

Eng. Family: KMT2.0T5FC19 Evap. Family: I

Eng. Type : <u>IL4</u> Liters (CID): <u>2.0 (121.9)</u>

ABBREVIATIONS

Ignition System	Exhaust Emissions Control System	Special Features
CA -Centrifugal Advance ECU -Electronic	AIP -Air Injection-Pump AIV -Air Injection-Valve DBC -Dual Bed Catalyst	CCV -Combustion Chamber Valve CFI -Central Fuel
Control Unit EI -Electronic	EGR -Exhaust Gas Recirculation EIC -Electronic Injection	Injection or Throttle Body
Ignition	Control (Diesel Only)	Injection -
ESAC-Electronic Spark Advance	EM -Engine Modification OC -Oxidation Catalyst OS -Oxygen Sensor	DID -Diesel Injection- Direct
Control VA -Vacuum	HOS -Heated Oxygen Sensor SPL -Smoke Puff Limiter or	DIP -Diesel Injection-
Advance	Throttle Delay	Prechamber EPFI-Electronic Port
VR -Vacuum Retard	TOC -Trap Oxidizer, Continual TOP -Trap Oxidizer, Periodical	Fuel Injection
	TWC -Three-Way Catalyst WUOC -Warm-Up Oxidation Catalyst	IC -Intercooler or Aftercooler
	WUTWC-Warm-Up Three-Way Catalyst	MPFI-Mechanical Port Fuel Injection
Fuel System	e .	OBD -On-Board Diagnostics
	-	SC -Supercharger
CFI, EPFI, MPFI, SF DID, DIP, HOS, OS	1,	SFI -Sequential Fuel Injection
nV-nVenturi Carbure	tor	TC -Turbocharger

Vehicle Models: Dodge Colt Vista 4WD & Plymouth Colt Vista 4WD

Engine : Front X Mid ___ Rear ___

VV-Variable Venturi Carburetor

Drive : FWD X RWD 4WD Full Time 4WD Part Time X

E.O. # <u>A-86-104</u>

	19 <u>89</u> AIR	RESOURCES	BOARD SUP	PLEMENTAL	DATA	SHEET	Page _	2/2
Passen	nger Cars	Ligh	-Duty Tru	cks X	Medi	um-Duty	Vehicle	s
Gas _	X	Dies	el					
Mfr.:	Mitsubi	ishi Motors	Corporati	on E	ing. Fa	amily: _	KMT2.0T	5FC19
Liter	(CID):	2.0 (121.9	Eng.	Type:	IL4			
Emissi	on Contro	l Sys.:E	GR+OS+TWC+	SFI				
(Speci	al Featur	es)						

Eng. Code	Vehicle Models (If coded see attachment) (Dyno Hp)	T/M. Type	ETW	Ign. System (ECU) Part No.	Fuel System Part No.	EGR Valve	Catalyst Part No.
CM-ZF ACM-ZF	Dodge Colt Vista 4WD Plymouth Colt Vista 4WD	M5	3250 3375	Distributor T1T42073 ECU E2T33771	Injector B210H Throttle Body AC50-106 ECU E2T33771 Air Flow Sensor E5T01472	K5T50282	MD130465

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.