### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER A-86-95 Relating to Certification of New Motor Vehicles

#### MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Mitsubishi Motors Corporation emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family	Displacement <u>Liters (Cubic Inches)</u>		Exhaust Emission Control Systems (Special Features)		
KMT2.0V5FC29	2.0	(121.9)	Exhaust Gas Recirculation Heated Oxygen Sensor Three-Way Catalyst (Electronic Port Fuel injection)		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides		
(Grams per Mile)	(Grams per Mile)	(Grams per Mile)		
0.39	7.0	0.4		

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
(Grams per Mile)	(Grams per Mile)	(Grams per Mile)
0.26	1.9	0.3

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

\_ day of April, 1988.

K. D. Drachand, Chief Mobile Source Division

E.O. # A-86-95

TC -Turbocharger

## 1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1/2

Manufacturer: <u>Mitsubishi Motors Corporation</u>

Eng. Family: KMT2.0V5FC29 Evap. Family: I

Eng. Type : <u>IL4</u> Liters (CID): <u>2.0 (121.9)</u>

#### ABBREVIATIONS

Ignition System	Exhaust Emissions Control System	Special Features
CA -Centrifugal Advance	AIP -Air Injection-Pump AIV -Air Injection-Valve	CCV -Combustion Chamber Valve
ECU -Electronic	DBC -Dual Bed Catalyst	CFI -Central Fuel
Control Unit	EGR -Exhaust Gas Recirculation	Injection or
EI -Electronic	EIC -Electronic Injection	Throttle Body
Ignition	Control (Diesel Only)	Injection
ESAC-Electronic	EM -Engine Modification	DID -Diesel
Spark	OC -Oxidation Catalyst	Injection-
Advance	OS -Oxygen Sensor	Direct
Control	HOS -Heated Oxygen Sensor	DIP -Diesel
VA -Vacuum	SPL -Smoke Puff Limiter or	Injection-
Advance	Throttle Delay	Prechamber
VR -Vacuum	TOC -Trap Oxidizer, Continual	EPFI-Electronic Port
Retard	TOP -Trap Oxidizer, Periodical	Fuel Injection
	TWC -Three-Way Catalyst	IC -Intercooler or
	WUOC -Warm-Up Oxidation Catalyst	Aftercooler
	WUTWC-Warm-Up Three-Way Catalyst	MPFI-Mechanical
		Port Fuel
		Injection
		OBD -On-Board
<u>Fuel System</u>		Diagnostics
		SC -Supercharger
CFI, EPFI, MPFI, SF	T,	SFI -Sequential
DID, DIP, HOS, OS		Fuel Ingection

Vehicle Models: Mitsubishi Galant

VV-Variable Venturi Carburetor

nV-nVenturi Carburetor

Engine : Front X Mid \_\_\_ Rear \_\_\_

Drive : FWD X RWD 4WD Full Time 4WD Part Time

E.O. # A-86-95

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 2/2

Passen	ger Cars X	_ Light-Dut	y Trucks	Me	dium-Duty	Vehicles
Gas _	X	Diesel	<u> </u>			
Mfr.:	Mitsubishi Mo	tors Corpor	ation	Eng.	Family: _	KMT2.0V5FC29
Liter	(CID): 2.0	(121.9)	Eng. Type:	IL4	<del></del>	
	on Control Sys	EGR+HOS	S+TWC+(EPFI)		•	

Eng. Code	Vehicle Models (If coded see attachment) (Dyno Hp)	T/M. Type	ETW	Ign. System (ECU) Part No.	Fuel System Part No.	EGR Valve	Catalyst Part No.
CM ACM	Mitsubishi Galant	M5	3125 3250	Crank Angle Sensor T1T49071 ECU E2T33373	Injector B240H Throttle Body AC60-100 ECU E2T33373 Air Flow Sensor E5T01871	K5T50681	MD137271

Comments: See page one for abbrebiations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.