State of California AIR RESOURCES BOARD

EXECUTIVE ORDERA-86-96 Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Mitsubishi Motors Corporation emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family		lacement Cubic inches)	Exhaust Emission Control Systems (Special Features)		
KMT2.0V5FC18	2.0	(121.9)	Exhaust Gas Recirculation Oxygen Sensor Three-Way Catalyst (Electronic Port Fuel Injection)		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides		
(Grams per Mile)	(Grams per Mile)	(Grams per Mile)		
0.39	7.0	0.4		

The following are the certification emission values for this engine family:

Hydrocarbons (Grams per Mile)	Carbon Monoxide (Grams per Mile)	Nitrogen Oxides (Grams per Mile)
0.24	1.8	0.2

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fiil Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Maifunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

_ day of April, 1988.

K. D. Drachand, Chief Mobile Source Division

E.O. # A-86-96

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1/2

Manufacturer: Mitsubishi Motors Corporation

Eng. Family: KMT2.0V5FC18 Evap. Family: I

Eng. Type : <u>IL4</u> Liters (CID): <u>2.0 (121.9)</u>

ABBREVIATIONS

Ignition System	Exhaust Emissions Control System	Special Features
CA -Centrifugal	AIP -Air Injection-Pump	CCV -Combustion
Advance	AIV -Air Injection-Valve	Chamber Valve
ECU -Electronic	DBC -Dual Bed Catalyst	CFI -Central Fuel
Control Unit	EGR -Exhaust Gas Recirculation	Injection or
EI -Electronic	EIC -Electronic Injection	Throttle Body
. Ignition	Control (Diesel Only)	Injection
ESAC-Electronic	EM -Engine Modification	DID -Diesel
Spark	OC -Oxidation Catalyst	Injec tion-
Advance	OS -Oxygen Sensor	Direct
Control	HOS -Heated Oxygen Sensor	DIP -Diesel
′VA - V acuum	SPL -Smoke Puff Limiter or	Injection-
Advance	Throttle Delay	Prechamber
VR -Vacuum	TOC -Trap Oxidizer, Continual	EPFI-Electronic Port
Retard	TOP -Trap Oxidizer, Periodical	Fuel Injection
	TWC -Three-Way Catalyst	<pre>IC -Intercooler or</pre>
	WUOC -Warm-Up Oxidation Catalyst	Aftercooler
	WUTWC-Warm-Up Three-Way Catalyst	MPFI-Mechanical
•		Port Fuel
		Injection
. •		OBD -On-Board
Fuel System		Diagnostics
		SC -Supercharger
CFI, EPFI, MPFI, S	FI,	SFI -Sequential
DID, DIP, HOS, OS		Fuel Injection
nV-nVenturi Carbur	etor	TC -Turbocharger

Vehicle Models: <u>Mitsubishi Galant</u>

VV-Variable Venturi Carburetor

Dodge Colt Vista & Plymouth Colt Vista \$

Engine : Front X Mid Rear

Drive : FWD X RWD 4WD Full Time 4WD Part Time

Revised: 5-20-88 \$

19 <u>89</u>	AIR	RESOURCES	BOARD	SUPPLEMENTAL	DATA	SHEET	Page	2/2
--------------	-----	-----------	-------	--------------	------	-------	------	-----

Passen	ger Cars	x	Light-D	uty Truc	cks	Me	dium-Duty	Vehicles	
Gas _	<u> </u>		Diesel	-			•	•	
			otors Cor	poration	1	Eng.	Pamily:	KMT2.0V5	FC18
	(CID):			Eng. 1		IL4			
Emissi	on Contro	ol Sys.	: EGR+	OS+TWC+S	FI			•	
(Speci	al Featu	res)							

Eng. Code	Vehicle Models (If coded see attachment)	T/H. Type	ETW	Ign. System (ECU)	Puel System	EGR Valve	Catalyst
	(Dyno Hp)			Part No.	Part No.	Part No.	Part No.
CM ACM	Mitsubishi Galant	M5	3000 3125	Distributor T3T64174	Injector B210H	K5T50381	MD130465
CA	Mitsubishi Galant	L4	3000 3125	ECU E2T33872	Throttle Body AC50-108 or AC50-105 ECU E2T33872	•	
					Air Flow Sensor E5T01471		
CM-Z ACM-Z	Dodge Colt Vista Plymouth Colt Vista	м5	3000	Distributor T1T42073	Injector B210H Throttle	K5T50282	MD130465
CA-Z ACA-Z	Dodge Colt Vista Plymouth Colt Vista	L3	3000 3125	E2T33771	Body AC50-106 ECU E2T33771		
	i				Air Flow Sensor E5T01472		

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Revised: 4-11-'88, 5-20-'88 \$