## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-16-107 Relating to Certification of New Motor Vehicles

## MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1990 model-year Mazda Motor Corporation emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family LTK1.8V5FCDO <u>Displacement</u>: 1.8 Liters (112 inches<sup>3</sup>)

Equipped with the following exhaust emission control systems:

Oxygen Sensor
Three-Way Catalyst
Multipoint Electronic Fuel Injection
On-Board Diagnostics (Exempted)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
<u>(Grams per Mile)</u>	(Grams per Mile)	(Grams per Mile)
0.39	7.0	0.4

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
(Grams per Mile)	<u>(Grams per Mile)</u>	<u>(Grams per Mile)</u>
0.12	1.9	0.1

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Code of Regulations, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" (Title 13, California Code of Regulations, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this  $\frac{q^{n}}{2}$  day of May,

K. D. Drachand, Chief Mobile Source Division

## E.O. # A-16-107

Manufacturer Mazda Motor Corporation		_ Engine Family _	LTK1	LTK1.8V5FCD0		
Evaporative Family		Engine Type	1-4	<u>.</u> , <u>.</u>		
		Liters (CIO)				
ABBREVIATIONS		•				
Ignition System	Exhaust Em	nissions Control S	ystem	Special Features		
CA-Centrifugal Advance ECU-Electronic Control Unit EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard  Fuel System  CFI, EPFI, MPFI, SFI, DID, DIP, HOS, OS nV-nVenturi Carburetor VV-Variable Venturi Carburetor	AIV-Air In EGR-Exhaus EIC-Electr (Dies EM-Engine SPL-Smoke Throttle TOC-Trap (DBC-Dual EOC-Oxidati TWC-Three-WUOC-Warm-WUTWC-Warm-OS-Oxygen	ijection - Pump ijection - Valve it Gas Recirculation conic Injection Con sel Only) Modification Puff Limiter or Delay Oxidizer, Continua Oxidizer, Periodica Sed Catalyst Jon Catalyst Jup Oxidation Catal Jup Three-Way Cat Sensor Jup Oxygen Sensor	l al lyst alyst	CFI-Central Fuel Injection or Throttle Body Injection EPFI-Electronic Port Fuel Injection MPFI-Mechanical Port Fuel Injection SFI-Sequential Fuel Injection DID-Diesel Injection Direct DIP-Diesel Injection Prechamber TC-Turbocharger SC-Supercharger IC-Intercooler or Aftercooler CCV-Combustion Chamber Valve OBD-On-Board Diagnosi	er	
VEHICLE MODELS: Mazda 323						
				•		
Engine: Front X Mid		ar <u></u>				

Manufact  Pass Car  Eng. Typ  Emission	RESOURCE: BOAL  urer Mazda Mo  s_X Lt-Duty  eLi  Control Sys.  Front_X Mid	Trucks ter (CID)	Med-Dut 1.8 (11 Abbry.)	En	cles Evap. Fami	LTK1.8V5F  Gas_X_Die  iyE  OBD)	sel
Eng. Code/ (Cert Std.)	Veh. Models (if Coded see Attachmt.)	Trans. Type: A-Auto M-Man.	Equiv. Test Weight	RLHP or DPA		EGR Syst. Part No.	Catalyst Part No.
CBPD-M (Std.: *)			2,750	6.0			
CBPD-MC (Std.: *)	·	M-5		6.6	Distributor BP05		
BPD-A (Std.: *)	Mazda 323		2,875	6.0	Control Uni	N/A	вр02
CBPD-AC (Std.: *)		À-4	-	6.6	BP10 18 881 A		
Certificatio Non-methane CO NOx Evap.						<u>.</u>	

Date o	# 1c	e elle		1

Revisions: