State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-305-2 Relating to Certification of New Motor Vehicles

AMERICAN LIMOUSINE MANUFACTURING, INC.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1992 model American Limousine Manufacturing, Inc. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: NZ64.6V5FAL6 <u>Displacement</u>: 4.6 Liters (281 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation
Dual Heated Oxygen Sensors
Dual Three-Way Catalysts (Two)
Sequential Multipoint Electronic Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The emission standards for this engine family in grams per mile are as follows:

<u>Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>		
0.39	7.0	0.7		

The certification emission values for this engine family in grams per mile are as follows:

Hydrocarbons	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>		
0.20	2.7	0.4		

BE IT FURTHER RESOLVED: That the listed models are certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Code of Regulations which includes recall liability up to 7 years or 75,000 miles for emission control components if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying to the optional NOx standard for passenger cars with a loaded vehicle weight over 5,250 pounds (Title 13, California Code of Regulations, Section 1960.1.5(a)(1)(C).

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." for the aforementioned model year (Title 13, California Code of Regulations, Section 1968).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2290).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this ______ day of February, 1992.

R. B. Summerfield

Assistant Division Chief Mobile Source Division

199,2 AIR	RESOURCES BOA	RD SUPP	LEMENTAL	DATA	SHEET E.O.	# <u>A-305-2</u>	Page
Manufactu	rerAMERICA	N LIMO	USINE M	FG.	ingine Family	NZ64.61	/5FAL6
Pass Car_	x Lt-Duty 1	ruck	Med-[uty Ve	hiclef	uel Type _{-G}	ASOLINE -
	pe <u>v8</u> Liter						
Emission (Use abbr	Control Sys. 8 eviations per	Specia SAE J19	11 Featur 930 Jun88	es <u>EG</u>	R/2H02S/21	WC(2)/SF	
Engine: F	ront <u>x</u> Mid	Rear_	· Dr	ive: F	WDRWD_x	_ 4WD-FT	4WD-PT
Code/	Veh. Models (If Coded see Attachmt.)	Type:	Test	RLHP	Ign.Sys. (PCME/PROM) Part No.	EGR Syst. Part No.	Catalyst Part No.
118SR05A	ALM Linco	'n					
220010311	St. Trope:	A4	5500			1	(-5E212-) FlVC-GA
	ALM Linco St. Trope	L					(-5E214-)
	tion Standa 0.39 7.0 0.7 2.0	rds					
(1) HP met	hod used to	deter	mine DI	A is	frontal a	rea	

Revisions: 042090