State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-609 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Ford Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: SFM2.5VJG1EA <u>Displacement</u>: 2.5 Liters (155 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters Three Way Catalytic Converter Dual Heated Oxygen Sensors Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (alternative in-use compliance standards in parentheses) for this engine family in grams per mile are:

Milos	Non-Methane	Carbon	Nitrogen
	Hydrocarbons	<u>Monoxide</u>	<u>Oxides</u>
<u>Miles</u>	0.25 (0.32)	3.4 (5.2)	0.4 (n/a)
50,000	0.31 (n/a)	4.2 (n/a)	n/a
100,000	0.31 (n/a)	, 10 2 (04) 05	

The certification exhaust emission values for this engine family in grams per mile are:

Miles_	Non-Methane	Carbon	Nitrogen
	Hydrocarbons	<u>Monoxide</u>	<u>Oxides</u>
50,000	0.13	1.0	0.3
100,000	0.16	1.3	n/a
100,000			

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 60 percent of the manufacturer's projected sales of 1995 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards time of the Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles with Three-Way Catalyst Systems and Feedback Control" (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models have been exempted from compliance with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles and Engines" pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(2.0) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 12 day of July, 1994.

R. B. Summerfield Assistant Division Chief

Mobile Source Division

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page ____ of ____ PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Evap Std: 50 Exh Std: Tier Veh Class(es) Single Cert S Exh Cert Fuel Fuel Type(s) Hybrid: Type Engine Confi	FORD MOTOR C K X Useful L -0 Tier-1 X : PC X LDT1 Std for Multi-C (s): Indo X F M85 C CNG LNG A B C guration: V-6 t X Mid. R (eg., EGR, MFI	TLEV LDT Class Eng Ph2 D CNG 1 Flex-F LPG APU Cy Displace	R/LLEV_2MD_Fam: iesel: l.PGOther other other icement:	Evap E ULEV	MDV2 MDV3 Decify: N/A, I 2282 or 40 Specify) Decify Ndecify Gaso Specify Liter D 4WD-FT SFI.2HO2S 27 abbreviations	Tier-0 MDV4 DT1, MDV1 CFR 86.11 oline_X rbine) //35 / 4WD-PT_ wc per SAE	MDV5
Engine Code/ CA/49ST/ 50ST	Veh. Models (If Coded see Attachmt.)	Trans. Type: A-Auto M-Man.	Test	RLHP or DPA @	Ign. Sys. (ECM/PCM) Part No. -12A650-	EGR Syst. Part No -9D475-	
2.5L 512TR05 N A N A 511TR05 N A N A	CONTOUR 3FA MYSTIQUE 4FA CONTOUR 3FA MYSTIQUE 4FA	61	3375 " " 3250 * 3375	5.2 5.2 5.2 5.7 5.7 5.7 5.7	94BB-EC " " 94BB-DB " "	14 14 54	94BBGB " " 94BBJA " "
* Tes	ndard tire DPA t at next high ion Standards	1					

ENGINE FAMILY: SFM2.5VJG1EA ISSUED: / 6-22-94 REVISED:

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page ___ of ___ PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

PAS	SENGER CARS, L	IGHT-DOI	1 110011-	_		C1 FA	_
				Eng. Fa	mmily SFM2.5VJ	SEM1045A	YPOA
Vanufacturer	FORD MOTOR CO	f- with	D /I	Evap Et	igine ramity;	m 0	Tier-1
	Manufacturer FORD MOTOR COMPANY Evap Std: 50K X Useful Life with R/L Evap Engine Family: SFM1045AYPOA Evap Std: 50K X Useful Life with R/L ULEV ZEV ; EPA Tier-0 Tier-1 Exh Std: Tier-0 Tier-1 X TLEV LEV MDV1 MDV2 MDV3 MDV4 MDV5 Veh Class(es): PC X LDT1 LDT2 MDV1 (specify: N/A, LDT1, MDV1, ETC.) Single Cert Std for Multi-Class Eng Fam: (specify: N/A, LDT1, MDV1, ETC.) Single Cert Std for Multi-Class Eng Fam: Orber (specify) M85						
Evap Std: Tier	.0 Tier-1_X	IDT	MDV	1 !	MDV2 MDV3	TTI MDV1	ETC.)
Veh Class(es)	: PC_X_ LDT1	Loce Eng	Fam:	(sp	ecity: N/A, L	CFR 86.113	-90 or -94
Single Cert S	td for Multi-C.	nasa biib	iesel: $\overline{13}$	CCR 2	282 01 40	_	
Exh Cert Fuel	(s): Indo X	NG L	PG 01	cher (s	pecity)	line X Di	lesel M85
D14-1	td for Multi-C. (s): Indo X P M85 C Dedicated CNG LNG A B C guration: V-6	Flex-F	ue11	Dual-Fu	el		eselM85
	CNGLNG ABC_ guration: V-6 t_X_MidRef (agEGR, MFI	APU CY	cle (e.g	., Otto), Dieser, 1	/	Cubic Inches
Hybrid: Type	AB	Displac	ement:	2.5/.	AUD FT	4WD-PT_	
Engine Config	guration:	ar Di	cive: FWD	X RWI	CET 2H02S 27	wc	2 - 01)
Engine: Front	t X Mid MFI	TC. CA	c): <u>EGR</u> .	TWC.	-bbrowiations	per SAE J	1930 Sep 91)
Exhaust ECS	guration: <u>V-6</u> t <u>X</u> Mid Re (eg., EGR, MFI	,,		(Use	abbreviacion		
					Ign. Sys.	EGR	atalyst
	Veh. Models	Trans.	Equiv.	RLHP	(ECM/PCM)		Part No.
Engine	(If Coded	Type:	Test	or	Part No.	Part No	010
Code/	see	A-Auto	Weight	DPA	-12A650-	-9D475-	-5E212-
CA/49ST/	Attachmt.)	M-Man.		@	12.10	 	
50ST	Accacian		t			1 1	ounn CB
				4.7	94BB-EC	F53EAA	948866
2.5L	CONTOUR 1FA	A	3375	5.2	14	"	
512TR05 N			\	4.7	и		 18
n N	MYSTIQUE 2FA	-	, "	5.2	*	•	
 A	n	n	\	1	1		94BBJA
		.,	3250	5.2	94BB-DB	F53EAA	# # DD D
511TR05 N	CONTOUR 1FA	M	3250 *	L	n	, "	l n
A		, ,	3230	5.2	**	, ",	
N	MYSTIQUE 2FA	, "	3375	5.7	"	, "	
A	•		1 33,0	1		F52F - AA	94BBJA
	174	М	3250	5.2	94BB-DD	יייי ביייייייייייייייייייייייייייייייי	н
511TR11 N	CONTOUR 1FA	, ,,	3250	5.7	"		11
A	L ame alter OTA		, n	5.2	" "		n
N			3375	5.7	, "	1	
A	.		1		1		
						ľ	1
)	1
			1			1	
			1				l l
				1	Į.	\	
0.00	l dowd rire DP/	١.	}				
@ Standard tire DPA.							
L T.	st at next high	her ETW	1	ļ		1	
* fe	St at here may		į		1	ļ	
Certification Standards							
Certification Standards 50K/100K							
MMUC.	0.25/0.31		1	1		1	
NMHC:	3.4/4.2						
CO:	0.4/						
NOx: EVAP:	2.0						
COLD CO						ı	R/C 2.5-9
COLD C.	 -			20.09	.17.02 - 1	•	·/ · · · · ·

ENGINE FAMILY: SFM2.5VJG1EA ISSUED: 6-22-94 REVISED: 4-13-95