State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-260 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: STY1.8VJG1GA Displacement: 1.8 Liters (107.5 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection

Exhaust Gas Recirculation

Oxygen Sensor

Three Way Catalytic Converter

Heated Oxygen Sensor

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides
50,000	0.25	3.4	0.4
100,000	0.31	4.2	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides
50,000	0.15	1.5	0.2
100,000	0.16	1.8	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles with Three-Way Catalyst Systems and Feedback Control" (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models have been exempted from compliance with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles and Engines" pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(2.0) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3 day of August, 1994.

R. B. Summerfield / Assistant Division Chief Mobile Source Division

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOY		LOYOL	OYOTA		Engine Fa	mily:	STY1.8VJG1GA
Evaporat.	ive Family:	STY104	7DYM00		Evap Std:	50K x Usef	ul Life with R/L
Fuh Ctd.	Tipr_0 Tipr_1	ነ 👽 ጥና!	FV 1	T TO CO	111 EV 7 EV	• የወኔ ጥሩል	י א דו א דו איי
Veh Clas	s(es): PC <u>x</u> Li	DT1	LDT2		MDV1MDV		
Single Co	ert Std for Mult	i-Class	Eng F	am:	(specify: N/	A, LDT1, MDV1	, MDV2, MDV3, MDV4)
Exh Cert	Fuel(s): Indo_x	Ph2	Di	esel:	13 CCR 2282	or 40 CFR 86	.113-90 or -94
	M85	CNG_	_ LP	G	Other (specif	y)	
Fuel Type	e(s): Dedicated_:	x_ Fle:	x-Fuel	D	ual-Fuel	Gasoline_x_	Diesel M85
	CNGLNO	G LI	PG	Other	(specify)		
Hybrid: 1	Type AB	c,	APU C	ycle (e.g., Otto, D	iesel, Turbin	e)
Engine Co	onfiguration: <u>I-</u>	<u>4</u> Di:	splace	nent:	1.8 /	Liters <u>107.5</u>	/ Cubic Inches
Engine:	Front <u>x</u> Mid	_ Rear .		Dr	ive: FWD <u>x</u>	RWD 4WD	FT 4WD-PT
Exhaust 1	ECS (eg., EGR, MI	FI, TC,	CAC):		SFI, E	GR, O2S, TWC, H	FT 4WD-PT D2S
				(use a	bbreviations	per SAE J1930	SEP91)
			·		7	· · · · · · · · · · · · · · · · · · ·	
		Trans.		DPA	Ignition	EGR	Catalytic
Code/	(If Coded see	Type:		or		System	converter
(Cert.	attachmt)	A or L		RLHP	Part No.	Part No.	Part No.
std.)		-Auto					
		M-Man.				,	
9	AE102L-AWMNKA	М5	2,750		*1	25620-16240	E16
10	AE102L-AEMNKA		2,750	7.1	89661-1A290		
	-DEMNKA				*2		
	-AWMNKA		2,875		_		
11	AE102L-AWMNKA		2,875		89661-02160		
12	AE102L-AEMNKA		2,750	7.8			
	-DEMNKA		:				
	-AWMNKA		2,875				
13		L4	2,875		*1	25620-16250	
14	AE102L-AEPNKA		2,875	7.1	89661-1A280		
	-DEPNKA				45		
	-AWPNKA			7.8	. *2		
	AE102L-AWPNKA		2,875		89661-02150	ļ	
16	AE102L-AEPEKA		2,875	7.8			
	-AEPNKA		1				
	-DEPEKA	į					
	-DEPNKA		į				
	-AWPNKA			8.5			
Comments	: Please refer t	o manuf	acture	er's HI	list for con	rect dyno tes	t HP setting

based on model and equipment.

Note *1 : Applied to the vehicle model produced in Japan.

*2 : Applied to the vehicle model produced in U.S. or Canada.

VEHICLE MODELS :

Corol	Corolla waqon		
AE102L-AEMNKA	AE102L-DEMNKA	AE102L-AWMNKA	
-AEPEKA	-DEPEKA	AE102L-AWPNKA	
-AEPNKA	-DEPNSA		

Page : 17.11-STY1.8VJG1GA-1

Issued : 04/04/94

Rev. 13: 04/03/95