State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-268-B Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: STY3.0VJGFEK <u>Displacement</u>: 3.0 Liters (182.7 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Exhaust Gas Recirculation Dual Heated Oxygen Sensors Three Way Catalytic Converter Heated Oxygen Sensor On-Board Diagnostic II

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (alternative in-use compliance standards in parentheses) for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (n/a)
100,000	0.31 (n/a)	4.2 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>
50,000	0.14	1.4	0.1
100,000	0.16	1.6	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 60 percent of the manufacturer's projected sales of 1995 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, Medium-Duty Vehicles and Engines" (Title 13, California Code Of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 💆

day of August, 1994.

R. B. Summerfield Assistant Division Chief Mobile Source Division

17.11.00 Supplemental data sheets

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufact	urer:	ATOYOTA		Engine Fa	mily:	STY3.OVJGFEK
						ul Life with R/Lx
						r-0 EPA Tier-1
						MDV4MDV5
						, MDV2, MDV3, MDV4)
•		_				113-90 or -94
_						
Fuel Typ	$e(s)$: Dedicated_	x Flex-Fuel	D	ual-Fuel	Gasoline_x_	DieselM85
Hybrid:						e)
						/ Cubic Inches
Exhaust	ECS (eg., EGR, M	FI, TC, CAC);		SFI, E	GR, 2HO2S, TW	-FT 4WD-PT
	•				per SAE J1930	
Engine	Vehicle Models	Trans. ETW	DPA	Ignition	EGR	Catalytic
Code/	(If Coded see	Type:	or	(ECM/PCM)	System	converter
	attachmt)		RLHP	Part No.	Part No.	Part No.
std.)		-Auto				
		M-Man.				
4	MCV10L-BTPGKA	L4 3,750	7.2	B9661-33440	25620-20010	P04
5	MCX10L-AEPGKA		5.9			1
	-AEPNKA	1	1	1		1
	-AESNKA					
	-AESGKA	3.750			!	!

Comments: Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

Page : 17.11-STY3.0VJGFEK-5.1

Issued: 07/21/94

17.11.00

VEHICLE MODELS :

ES300 MCV10L-BTPGKA AVAION MCX10L-AEPGKA MCX10L-AEPNKA MCX10L-AESGKA MCX10L-AESNKA

Page : 17.11-STY3.0VJGFEK-5.2

Issued : 07/21/94