State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-196 Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: STK1.8VJG1EK Displacement: 1.8 Liters (112 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection On-Board Diagnostic II

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
50,000	0.25	3.4	0.4	
100,000	0.31	4.2	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
50,000	0.13	1.4	0.1	
100,000	0.14	1.6	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with these standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 6 da

_ day of June, 1994.

R. B. Summerfield Assistant Division Chief

Mobile Source Division

1995 AIR F	RESOURCES BOA	ARD SUPPLEN	MENTAL	DATA SH	FET FO# 4 //	107		
1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET E.O.# Q 16 - 196 page of Manufacturer								
Passenger Car X (PC) Light-Duty Truck (T1/T2) Medium-Duty Vehicle (M1/M2/M3/M4/M5)								
Stds Type: Tier 1 (Tier 0/1, AB965, TLEV LEV LISTO Medium-Duty Vehicle (M1/M2/M3/M4/M5)								
Stds Type: Tier 1 (Tier 0/1, AB965, TLEV, LEV, ULEV) Vehicle Type (FFV, HEV(Type A/B/C)): N/A Fuel Type Unleaded Evaporative Family STK1178BYM11								
Engine Config	. <u>I-4</u>	1	3a-/OID)	⊏vapora	tive Family	STK1178B	YM11	
Engine: Fro	nt X Mid	Bear 1	iner(CID)	1.8	(112.3)			
Exhaust ECS	& Special Feature	neal [Juve: F	WD <u>x</u>	RWD 4WD)-FT 4	IWD-PT	
(use abbreviat	Exhaust ECS & Special Features (incl. CARB, MFI, etc.) TWC/AO2S/EGR/SFI / 0 BD 2 (use abbreviations per SAE 1930 MAY91)							
Evap Std:	Evap Std: 100 K Single Cert Std for Multi-Class Eng Fam: N/A							
Exh Cert Fue	l(s): Phase ?	Fuel Tune	Multi-Ci	ass Eng I	am: <u>N/A</u>	٠		
APU Cycle:	Otto	_ ruci Type	(2): <u>(</u>	Jasoline	Hybrid: N/	<u>A</u>		
- 3			•					
Engine Code	Malain Indiana						r•	
(Cert. Std.)	Vehicle Models (if coded see	Trans, Type A-automatic	ETW	DPA	Ignition	EGR	Catalyst	
15556	attachment)	M-manual	<u> </u>	or RLHP	(ECM/PCM) Part No.	System Part No.	Part. No.	
1BPD2AAN	Mazda Protege	M5	2875	6.3	Distributor: B6BF	EGR	BPD3	
1BPD2AAA				6.9	ECU:	Control	21.03	
IBPDTAAN		A4		6.3	BPD5 18 881A			
IBPDTAAA			3000	6.9	BPD6 18 881A	B6BF		
1	J		•			DODI		
N=n								
Certification S	táňdard: NMHC		00					
50,000 miles	0.25 g/r	nile 3.4	CO g/m	ile (NOx 0.4 g/mile	EVAP.		
100,000 miles	0.31 g/n	nile 4.2			0.4 g/mile	2.0 g/te	est_	
at 2500 rpm N/L at idle								
Idle HC	220 ppm	100 ppm						
1.0 %								
Revisions: 1290								