

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-23-171  
Relating to Certification of New Motor Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: SHN2.3VJGEEA Displacement: 2.3 Liters (138 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

- Three Way Catalytic Converter
- Heated Oxygen Sensor
- Exhaust Gas Recirculation
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (alternative in-use compliance standards in parentheses) for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (n/a)
100,000	0.31 (n/a)	4.2 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>
50,000	0.11	1.1	0.2
100,000	0.13	1.3	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 60 percent of the manufacturer's projected sales of 1995 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles with Three-Way Catalyst Systems and Feedback Control" (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O. # A-23-171

Page 1 of 1

Manufacturer HONDA Exh Engine Family: SHN2.3VJGEEA  
 Evap Std: 50K X Useful Life with R/L\_\_\_ Evap Engine Family: SHN1100BYMOR  
 Exh Std: Tier-0\_\_\_ Tier-1 X TLEV\_\_\_ LEV\_\_\_ ULEV\_\_\_ ZEV\_\_\_ ; EPA Tier-0\_\_\_ Tier-1 X  
 Veh Class(es): PC X LDT1\_\_\_ LDT2\_\_\_ MDV1\_\_\_ MDV2\_\_\_ MDV3\_\_\_ MDV4\_\_\_ MDV5\_\_\_  
 Single Cert Std for Multi-Class Eng Fam: N/A  
 Exh Cert Fuel(s): Indo X Ph2\_\_\_ Diesel: 13 CCR 2282\_\_\_ or 40 CFR 86.113-90\_\_\_ or -94\_\_\_  
 M85\_\_\_ CNG\_\_\_ LPG\_\_\_ Other\_\_\_  
 Fuel Type(s): Dedicated X Flex-Fuel\_\_\_ Dual-Fuel\_\_\_ Gasoline X Diesel\_\_\_ M85\_\_\_  
 CNG\_\_\_ LNG\_\_\_ LPG\_\_\_ Other\_\_\_  
 Hybrid: Type A\_\_\_ B\_\_\_ C\_\_\_, APU Cycle\_\_\_  
 Engine Configuration: I-4 Displacement: 2.3 Liters 138 Cubic Inches  
 Engine: Front X Mid\_\_\_ Rear\_\_\_ Drive: FWD X RWD\_\_\_ 4WD-FT\_\_\_ 4WD-PT\_\_\_  
 Exhaust ECS: TWC/HO2S/EGR/SFI

Engine Code (also list CA/ 49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type A-automatic M-manual	ETW	DPA	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
SRA1/1 (50ST)	Prelude Si	M	3125	7.6 (MI)	EI Distributor: TD-61U ECM:37820-P14 -A12	EGR Valve: 11C	TU
SRA3/1 (50ST)	Prelude Si	A	3250	7.6 (MI)	EI Distributor: TD-61U ECM:37820-P14 -A62		

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O. # A-23-172  
Page 17 of 1

Manufacturer HONDA Exh Engine Family: SHN2.2VJG1GA  
 Evap Std: 50K\_\_\_ Useful Life with R/L X Evap Engine Family: SHN1100AYM1B  
 Exh Std: Tier-0\_\_\_ Tier-1 X TLEV\_\_\_ LEV\_\_\_ ULEV\_\_\_ ZEV\_\_\_ ; EPA Tier-0\_\_\_ Tier-1\_\_\_  
 Veh Class(es): PC X LDT1\_\_\_ LDT2\_\_\_ MDV1\_\_\_ MDV2\_\_\_ MDV3\_\_\_ MDV4\_\_\_ MDV5\_\_\_  
 Single Cert Std for Multi-Class Eng Fam: N/A  
 Exh Cert Fuel(s): Indo\_\_\_ Ph2 X Diesel: 13 CCR 2282\_\_\_ or 40 CFR 86.113-90\_\_\_ or -94\_\_\_  
 M85\_\_\_ CNG\_\_\_ LPG\_\_\_ Other\_\_\_  
 Fuel Type(s): Dedicated X Flex-Fuel\_\_\_ Dual-Fuel\_\_\_ Gasoline X Diesel\_\_\_ M85\_\_\_  
 CNG\_\_\_ LNG\_\_\_ LPG\_\_\_ Other\_\_\_  
 Hybrid: Type A\_\_\_ B\_\_\_ C\_\_\_, APU Cycle\_\_\_  
 Engine Configuration: I-4 Displacement: 2.2 Liters 132 Cubic Inches  
 Engine: Front X Mid\_\_\_ Rear\_\_\_ Drive: FWD X RWD\_\_\_ 4WD-FT\_\_\_ 4WD-PT\_\_\_  
 Exhaust ECS: TWC/HO2S/EGR/SFI

Engine Code (also list CA/ 49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type A-automatic M-manual	ETW	DPA	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
SPL1/1 (CA)	Accord EX Coupe Accord EX Sedan	M	3375	7.4 (MI)	EI Distributor: D4T92-04 ECM:37820-POH -L00	EGR Valve: 11M	UB
SPL3/1 (CA)	Accord EX Coupe Accord EX Sedan	A	3375	7.4 (MI)	EI Distributor: D4T92-04 ECM:37820-POH -L50		