

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-314-7  
Relating to Certification of New Motor Vehicles

KIA MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Kia Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: SKM1.8VJG1EK Displacement: 1.8 Liters (112 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection  
Three Way Catalytic Converter  
Heated Oxygen Sensor  
Exhaust Gas Recirculation  
On-Board Diagnostic II

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Hydrocarbons</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> |
|--------------|---------------------------------|------------------------|------------------------|
| 50,000       | 0.25                            | 3.4                    | 0.4                    |
| 100,000      | 0.31                            | 4.2                    | n/a                    |

The certification exhaust emission values for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Hydrocarbons</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> |
|--------------|---------------------------------|------------------------|------------------------|
| 50,000       | 0.19                            | 1.8                    | 0.2                    |
| 100,000      | 0.20                            | 2.1                    | n/a                    |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 6th day of April, 1995.

  
R. B. Summerfield  
Assistant Division Chief  
Mobile Source Division

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Kia Motors Corporation Exh Engine Family: SKM18V1G1EK  
 Evap Std: 50K  Useful Life with R/L  Evap Engine Family: SKM1178BYMU1  
 Exh Std: Tier-0  Tier-1  TLEV  LEV  ULEV  ZEV  ; EPA Tier-0  Tier-1   
 Vehicle Class(es): PC  LDT1  LDT2  MDV1  MDV2  MDV3  MDV4  MDV5   
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Exh Cert Fuel(s): Indo  Ph2  Diesel: 13 CCR 2282  or 40 CFR 86.113-90  or -94   
 M85  CNG  LPG  Other (Specify) \_\_\_\_\_  
 Fuel Type(s): Dedicated  Flex-Fuel  Dual-Fuel  Gasoline  Diesel  M85   
 CNG  LNG  LPG  Other (specify) \_\_\_\_\_  
 Hybrid: Type A  B  C  APU Cycle (e.g., Otto, Diesel, Turbine) \_\_\_\_\_  
 Engine Configuration: I-4 Displacement: 1.8 Liters 112 Cubic Inches  
 Engine: Front  Mid  Rear  Drive: FWD  RWD  4WD-FT  4WD-PT   
 Exhaust ECS (e.g., EGR, MFI, TC, CAC): SEI, TWC, HO2S, EGR, OBD II  
 (use abbreviations per SAE J1930 SEP91)

| Engine Code<br>(Cert Std.) | Vehicle Models<br>(if coded see<br>attachment) | Trans. Type<br>A-automatic<br>M-manual | ETW<br>or<br>Test Wt | DPA<br>or<br>RLHP | Ignition<br>(ECM/PCM)<br>Part No. | EGR<br>System<br>Part No.         | Catalyst<br>Converter<br>Part No. |
|----------------------------|--|--|----------------------|-------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| BPDC-MN                    | Kia Sephia                                     | M-5                                    | 2875                 | 5.7               | Distributor<br>: B6BF             | EGR<br>Control<br>Valve<br>: B6BF | BPA3                              |
| BPDC-MC                    |  |  | 2875                 | 6.3               | ECU: ZT82                         |                                   |                                   |
| BPDC-AN                    |  | L-4                                    | 2875                 | 5.5               | Distributor<br>: B6BF             |                                   |                                   |
| BPDC-AC                    |  |  | 2875                 | 6.0               | ECU: ZT83                         |                                   |                                   |

## Certification Standards:

|                | NMHC            | CO         | NOx        | EVAP.      |
|----------------|-----------------|------------|------------|------------|
| 50,000 mile :  | 0.25 g/mile     | 3.4 g/mile | 0.4 g/mile | 2.0 g/test |
| 100,000 mile : | 0.31 g/mile     | 4.2 g/mile | 0.6 g/mile | ---        |
|                | at 2500 rpm N/L | at idle    |            |            |
| Idle HC :      | 220             | 100        |            |            |
| Idle CO :      | 1.2             | 1.0        |            |            |

Issue Date : January 14, 1995

Revised :

Sec.17.02.00.00-2