State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-318-1 Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS AUSTRALIA, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Mitsubishi Motors Australia, Ltd. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: SML3.0V8G1EA <u>Displacement</u>: 3.0 Liters (181.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation
Three Way Catalytic Converter
Dual Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection
Dual Warm-Up Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Mi <u>les</u>	Non-Methane	Carbon	Nitrogen	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
50,000	0.25	3.4	0.4	
100,000	0.31	4.2	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
50,000	0.13	1.8	0.1	
100,000	0.18	2.1	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles with Three-Way Catalyst Systems and Feedback Control" (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models have been exempted from compliance with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles and Engines" pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(2.0) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 26 day of July, 1994.

R. B Summerfield Assistant Division Chief Mobile Source Division

E.O.#_A-318-1

199 5 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page 1 of 1

Manufacture	r: MITSUBISHI MO	TORS AUSTRALIA	LTD Ex	h Engin	e Family: SML	3.0V8G1EA	
Evap Std:	50K <u>X</u> Useful	Life with R/L_	Ev.	ap Engi	ne Family: SMT.	1054AVMOD	
Exh Std: Tie	er-0Tier-1	X TLEVLE	 V ULI	EV :	ZEV : FPA	Tier-O	Tier-1
Veh Class(es	s): PC <u>X</u> LDT1	LDT2	MDV1	MDV	2 MDV3	MDV4	MD//E
Single Cert	Std for Multi-Cla	ass Eng Fam:	N/A (si	ecify:	N/A IDTI MD	1.01.1 .V.1 MDV.2	NDA2
Exh Cert Fue	el(s): Indo <u>x</u>	Ph2 Diese	1: 13 CCF	2282	or 40 CED 0	6 112 00	MUV3, MUV4)
	M85 (CNG LPG	Other	/snecii	fy)	0.113-30	_ or -94
Fuel Type(s)	: Dedicated_X F	lex-Fuel []ual-Euel	(Special	Gasoline	V Dia1	1405
	CNGLNG	LPG Other	· (spacif	<u> </u>	gazot the_	v Diesei	M85
Hybrid: Type	A B C,	APII Cycle (e	d Otto	J)	1 Tunking)	· · · · · · · · · · · · · · · · · · ·	
ngine Confi	guration: V6	Displacement:	g., otto /	3 0	:i, iurbine) <u>. </u>	/ 101 / 0	
Engine: From	t X Mid	Roar	Daires	FUD V	Liters	<u>/ 181.4</u> (ubic Inches
Exhaust FCS	(eg., EGR, MFI, T	C CACL EGR	+ 2HU36(7 NU A	, KWU 4)	VU-F1	4WD-PT
	(03., 650, 10.1, 1	c, cac)	(use a	bbrevia	tions per SAE	J1930 SEP	91)
Engine Code	Vehicle Models	Trans. Type		DPA			
(also list	(if coded see	A-automatic	or	or	Ignition (ECM/PCM)	EGR System	Catalytic Converter
<u>CA/49ST/50ST</u>	attachment)	M-manual	Test Wt	RLHP	Part No.	Part No.	Part No.
ACA-5	MITSUBISHI	A	4000	0.5	D. 7.000		
(CA)	DIAMANTE WAGON	A	4000	8.5	DISTRIBUTOR: TST 42771	EGR VALVE	FRONT RH: MR127572
					ECM:	SOLENOID	
İ					MD311684	MD925902	
				j			REAR
							MR925699
		ļ					
				ł			
						:	
-				ľ	:		
ļ			1				
		İ		ľ			
ate Issued:	04.11.94						
evisions:		1		1		1	
	· · · · · · · · · · · · · · · · · · ·					_1_	