File

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-158-A Relating to Certification of New Motor Vehicles

MERCEDES-BENZ AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mercedes-Benz AG exhaust emission control systems are certified as described below for passenger cars:

<u>Fuel Type</u>: Gasoline

Engine Family: TMB6.0VJGFEK Displacement: 6.0 Liters (365 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Secondary Air Injection Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (Two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

	Non-Methane	Carbon	Nitrogen	Carbon
<u>Miles</u>	<u>Hydrocarbons</u>	Monoxide	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100,000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	Carbon <u>Monoxide (20⁰F)</u>
50,000	0.14	1.2	0.1	3.3
100,000	0.14	1.3	0.1	n/a

MERCEDES-BENZ AG

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

MERCEDES-BENZ AG

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label-Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 25 day of September 1995.

R. B. Summerfield Assistant Division Chief Mobile Source Division

E.O.#<u>A-3-158-A</u>



.

•

•

199<u>6</u> MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page_/____ PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES Page_/____

Manufacturer: <u>Mercedes-Benz</u> Exh Eng Fam: <u>TMB6.0VJGFEK</u> Evap Fam: <u>TMB1030AYMA0</u>
All Eng Codes in Eng Fam: CA 49S 50S_X AB965
Exh Std: CA Tier-1_XLEVULEVZEV; US EPA Tier-1_X
Evap Std: 50K_X_Useful Life with R/L In-Use Exh Std: Full In Use Alt In Use_X
Veh Class(es): PC_X_LDT1LDT2MDV1MDV2MDV3MDV4MDV5
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel
CNGLNGLPG M85 Other (specify)
Emiss Test Fuel(s): Indo <u>X</u> Ph2CNGLPGM85Other (specify)
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
Service Accum: Std AMA <u>X</u> Mod AMAMfr ADPOther (specify)
NMOG Test Procedure: N/A_XStdEquivR/L Test Proc: SHEDPt Source
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine):
Engine Configuration: <u>v-12</u> Displacement: <u>6.0 / Liters 365 / Cubic Inches</u>
Valves per Cylinder: Rated HP: 389 @ 5200 RPM
Fncine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT
Maust ECS (e.g., MFI, EGR, TC, CAC): <u>SFI/AIR/2H02S(2)</u> 2TWC/OBDII
(use abbreviations per SAE 11920 SEPOI)

(use abbreviations per SAE J1930 SEP91)

Engine Code (also list CA/49ST/50ST	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
M120-3	SL600	A5	4750	6.6	0205452232		129 490 48 129 490 47
							129 490 21 1 129 490 20 1
\sim							
ate Issued:							