State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-7-187 Relating to Certification of New Motor Vehicles

VOLKSWAGEN AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Volkswagen AG exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TVW2.8V8GFGM <u>Displacement</u>: 2.8 Liters (170 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Three Way Catalytic Converter Heated Oxygen Sensors (Two)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

Mi <u>les</u>	Non-Methane	Carbon	Nitrogen	Carbon
	Hydrocarbons	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100,000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Mi <u>les</u>	Non-Methane	Carbon	Nitrogen	Carbon
	Hydrocarbons	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.10	1.0	0.1	4.6
100,000	0.10	1.0		n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

R. B. Summerfield

Assistant Division Chief Mobile Source Division

PAGE NO.: 17.05. -01 E.O.# A-7-187 Page 1 of 1

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDUM-DUTY VEHICLES

All Eng Codes i Exh Std: CA Ti Evap Std: 50K Veh Class(es): Single Cert Std Fuel Type(s): I Emiss Test Fuel Service Accum:	Std AMA X	with R/ LDT2_ Eng Fa ex-Fuel LPG_ h2_ C 3 CCR 2	MD' Am: N/A Du M85 NG I 282	ULE In-us V1(spec al-Fue Other PG 40 Mfr A	V ZEV e Exh Std: Fu MDV2 M cify: N/A, LDT el Bi-Fuel c (specify) M85 Other CFR 86.113-90 DP Other	; US EPA	A Tier-1_X Alt In Use X MDV5 , MDV3, MDV4) X Diesel R 86.113-94 Pt Source n.a
	ъ C	APU CVC	te le.	4., ~~			
Fraine Config.	6, V	Dis	splacem	ent: _	2.8 111	Erb	-
Valves per Cyl	linder:2				** *DDIT	ייי – משט–דיי	4WD-PT
Engine: Front	Linder: 2 X Mid Eg., EGR, MFI, To	Rear _	D	rive:	WD X RWD	HO25(2)	
Exhaust ECS (eg., EGR, MFI, T	C, CAC,	etc.)		se abbreviation	ons per SAE 19	30 SEP91)
						FGR	Catalytic
Engine Code		Trans. Type		DPA or	(/ co. r)	System	Converter
(also list CA/49ST/50ST	(if codded see .	A-auto M-man.	Test WT	RLHP			Part No.
AAA	Jetta GLX VR6	м	3,250	7.0	021 906 258 A	-	1HM 131 701 H
	Golf GTI VR6	M	3,125	7.0	021 906 258 A	_	1HM 131 701 H
50 ST AAA 50 ST	Jetta GLX VR6	A .	3,250	6.3	021 906 258 A	-	1HM 131 701 H
AAA-B 50 ST	Passat GLX VR6 sedan/wagon	A	3,500	6.2	021 906 258 B	-	1HM 131 701 H
AAA-B 50 ST	Passat GLX VR6	М	3,500	6.8	021 906 258 B	-	1HM 131 701 H
AAA-B 50 ST	Passat GLX VR6 sedan	м	3,375	6.8	021 906 258 B	-	1HM 131 701 H
					-		
						<u> </u>	·
Date Issued	d: 06-20-95	<u> </u>					

Revisions: